Form 9-331 Dec. 1973

REPAIR WELL

ABANDON\*

(other)

PULL OR ALTER CASING MULTIPLE COMPLETE **CHANGE ZONES** 

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Form A	pproved		
Budget	Bureau	No.	42-R142

<b>5.</b> L	EASE SF 079386
6. 1	F INDIAN, ALLOTTEE OR TRIBE NAME
	JNIT AGREEMENT NAME San Juan 28-6 Unit
	FARM OR LEASE NAME San Juan 28-6 Unit
	VELL NO. 94A
	FIELD OR WILDCAT NAME So.Blanco PC & Blanco MV
1	SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec.36, T-28-N, R-6-W, NMPM
	COUNTY OR PARISH 13. STATE Rio Arriba NM
14. /	API NO.

	l	
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 28-6 Unit	
1 oil gas —	8. FARM OR LEASE NAME San Juan 28-6 Unit	
well well other	9. WELL NO. 94A	
2. NAME OF OPERATOR El Paso Natural Gas Company		
	10. FIELD OR WILDCAT NAME   So.Blanco PC & Blanco M	
3. ADDRESS OF OPERATOR PO BOX 289, Farmington, NM 87401		
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 36, T-28-N, R-6-W, NM	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)		
AT SURFACE: 1090'S, 850'E AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE Rio Arriba NM	
AT TOTAL DEPTH:	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6360 GL	
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF	RECEIVED	

(NOTE: Report results of multiple completion or zone AUG 2change of Form 9-330.)

5. GEOLOGICAL SUPERFY MINGTON, N

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded well. Drilled surface hole. Ran 5 jts. 8-16-82 9 5/8", 36#, K-55 surface casing, 205' set at 219'. Cemented with 130 cu.ft. cement. Circulated to surface. WOC 12 hours, held 600#/30 minutes.



Subsurface Safety Valve: Manu. and Typ	e	Set @ F
18. I hereby certify that the foregoing is SIGNED Susce	true and correct	ATE August 20, 1982
APPROVED BY	(This space for Federal or State office use)  TITLE	ACCEPTED FOR RECORD

AUS 20 1982