

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with applicable State requirements)

At surface 1190'N, 1130'W

At top prod. interval reported below

At total depth

14. PERMIT NO. BUREAU OF LAND MANAGEMENT
DATE ISSUED FARMINGTON RESOURCE AREA

5. LEASE DESIGNATION AND SERIAL NO.

SF 079250

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-5 Unit

8. FARM OR LEASE NAME

San Juan 28-5 Unit

9. WELL NO.

28A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC., T., R., N., OR BLOCK AND SURVEY OR AREA

Sec. 17, T-28-N, R-5-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

15. DATE SPUDDED 7-31-85 16. DATE T.D. REACHED 9-3-85 17. DATE COMPL. (Ready to prod.) 9-13-85 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 6660' GL 19. ELEV. CASINGHEAD 6660'

20. TOTAL DEPTH, MD & TVD 6210' 21. PLUG BACK T.D., MD & TVD 6203' 22. IF MULTIPLE COMPL., HOW MANY* One 23. INTERVALS DRILLED BY Rotary 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 5384-6148' (Blanco Mesa Verde) 25. WAS DIRECTIONAL SURVEY MADE No

26. TYPE ELECTRIC AND OTHER LOGS RUN Densilog Linear Porosity GR; Ind. Electrolog; Densilog Neutron GR; Temp. Log-GR; GR-C-L; Ind. Elec. GR; Temp Survey

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	36.0#	221'	12 1/4"	130 cu ft	
7"	20.0#	3726'	8 3/4"	282 cu ft	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)
4 1/2"	3553'	6210'	463 cu ft	

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 3/8"	6129'	

31. PERFORATION RECORD (Interval, size and number) 5854, 5866,

5890, 5896, 5937, 5950, 5985, 6010, 6034, 6045, 6052, 6078, 6103, 6123, 6133, 6148, w/16 SPZ. 2nd stage 5384, 5403, 5411, 5419, 5518, 5622, 5629, 5638, 5644, 5650, 5659, 5750, 5754, 5758, 5762, 5766, 5770, 5789,

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5854-6148	89,000# 20/40 sand&109,584 gals wt
5384-5821	62,000# 20/40 sand&149,946 gals slickwater

33. 5794, 5802, 5807, 5817, 5821 w/23 SPZ. PRODUCTION

DATE FIRST PRODUCTION 9-3-85 PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing WELL STATUS (Producing or shut-in) Shut in

DATE OF TEST 9-13-85 HOURS TESTED 3 Hrs. CHOKE SIZE 3/4" PROD'N. FOR TEST PERIOD 0 OIL—BBL. 551 MCF GAS—MCF. 0 WATER—BBL. 0 GAS-OIL RATIO 0

FLOW. TUBING PRESS. SI 457 CASING PRESSURE SI 963 CALCULATED 24-HOUR RATE 0 OIL—BBL. 3961 GAS—MCF. 0 WATER—BBL. 0 OIL GRAVITY-API (CORR.) 0

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Shut in to be Sold

TEST WITNESSED BY

Sonny Paul

35. LIST OF ATTACHMENTS

Temp Survey

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Drilling Clerk

DATE

9-24-85

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Chacra	4535'	5360'	Gry fn grn silty, glauconitic sd stone w/drak gry shale	Chacra Mesa Verde Menefee Point Lookout		
Mesa Verde	5360'	5420'	Gry, fine-grn, dense sil ss., carb sh & coal			
Menefee	5420'	5740'	Gry, fine-grn s, carb sh & coal			
Point Lookout	5740'	6210'	Gry, very fine sil ss w/frequent sh breaks			