Form	3160	-5
(Nove	mber	1983)
(Form	erly	9 - 331)

REPAIR WELL

(Other)

UNITED STATES DEPARTMENT OF THE INTERIOR (Other in verse side)

SUBMIT IN TRIPLICATE. (Other instructions on re-

Form approved. Budget Bureau No. 1004-0135

Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO.

SF 079519A

BUREAU OF	<u>LAND</u>	<u>MAN</u> AGEMENT	/

SUNDRY NOTICES AND REPORTS ON WELLS

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	
OIL GAS WELL WELL OTHER	7. UNIT AGREEMENT NAME San Juan 28-5 Unit
2. NAME OF OPERATOR El Paso Natural Gas Company	8. FARM OR LEASE NAME San Juan 28-5 Unit
3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499	9. WBLL NO. 48A
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1670'S, 1460'E	10. FIELD AND POOL, OR WILDCAT Blanco Mesa Verde
EIVED	11. SEC. T., R., M., OR BLK. AND Sec. 22, T-28-N, R-5-V N.M.P.M.
14. PERSUIT 19. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE

SEY

N.M. E

12. COUNT

RIO A

OF LAND MANAGE OF INTENTION TO:

PCLL OR ALTER CASING

BHOUT CO.

BHOUT CO.

BHOUT CO.

N.M. E

12. COUNT

RIO A

RIO A

BUBBBOOT

BHOUT CO.

BHOUT CO.

BHOUT CO.

BHOUT CO.

BHOUT CO.

N.M. E

12. COUNT

RIO A

RIO A

RIO A

BUBBBOOT

BHOUT CO.

BHOUT CO Rio Arriba NM SHOOT OR ACIDIZE ABANDON* SHOOTING OR ACIDIZING

CHANGE PLANS

REPAIRING WELL ALTERING CARING ABANDONMENT*

(Norz: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and gones pertinent to this work.)

9- 9-85 Cleaned out to 6464'. Pressure tested casing to 3500 psi, held ok. Perforated 6136', 6142', 6154', 6192', 6211', 6226', 6250', 6272', 6277', 6282', 6305', 6366', 6378', 6390' with 1 spz. Fraced with 69,000# sand and 105,322 gal. wtr. Flushed with 8190 gal.wtr.

(Other)

9-10-85 Perforated 2nd stage at 5978', 5982', 5985', 5992', 5996', 6000', 6004', 6008', 6012', 6016', 6041', 6045', 6049', 6053', 6060', 6065', 6087', 6092', 6097', 6114' w/l spz. Fraced with 44,000# sand and 119,028 gal. wtr. Flushed with 8106 gal.wtr. Perforated 4825', 4831', 4838', 4895', 4900', 4970', 4977', 4985', 4993', 5174', 5361', 5368', 5530', 5596', 5613', 5625', 5635', 5643' w/l spz. Fraced with 54,000# sand and 121,674 gal. wtr. Flushed with 7560 gal. wtr.

9-13-85 Cleaned out to PBTD. Set 4 1/2" bridge plug at 4080'. Perforated one squeeze hole @ 3380'. Squeeze cemented Ojo Alamo with 250 sks. Class "B" with 2% calcium chloride (295 cu.ft.). WOC.

9-14-85 Cleaned out to below squeeze. Pressure tested casing, did not Squeeze cemented with 150 sks. Class "B" with 2% calcium chloride (177 cu.ft.). WOC.

9-15-85 Cleaned out to below squeeze. Pressure tested casing to 1500 psi, held ok. Cleaned out to PBTD. Ran tbg.

8. I hereby certify that the foregoing is true and correct SIGNED Daggy Loak.	TITLE	Drilling Clerk	9-24-85
(This space for Federal or State office use)			
CONDITIONS OF APPROVAL, IF ANY:	TITLE .		DATE
		DIV.	Minorum Resultinue AMÉA
*Se	e Instruct	tions on Reverse Side	A Third Control of the Control of th