Form 3160-5

UNITED STATES

SUBMIT IN TRIPLICATE.

Form approved. Budget Bureau No. 1004-0135

(Formerly 9-331)	DEPARTMENT OF T	HE INTERIOR (Other Inst	ructions on re- 5. LEASE DESIGNATION AND SERIAL NO.
, , , , , , , , , , , , , , , , , , , ,	BUREAU OF LAND A	▲ .	SF 079519A
(Do not use this	DRY NOTICES AND form for proposals to drill or to Use "APPLICATION FOR PERM	deepen or plug back to a different	6. IF INDIAN, ALLOPTEE OR TRIBE NAME
1. OIL - CAR	отнев	A . (7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	El Paso Natural G	EUREAU OF LAND M FARMINGTON RESOLUTION	ANAGEMENT San Juan 28-5 Unit
3. ADDRESS OF OPERATOR		1289,Farmington,NM	
4. LOCATION OF WELL (R See also space 17 belo	eport location clearly and in acco	rdance with any State requirements.	Basin Dakota 11. SEC., T., R., M., OR BLK. AND Sec. 20, 1-28-N, R-5-W NMPM
14. PERSIT NO.	15. ELEVATIONS	(Show whether DF, RT, GR, etc.) 6776 GL	12. COUNTY OF PARISH 13. STATE Rio Arriba MM
16.	Check Appropriate Box	To Indicate Nature of Notice,	Report, or Other Data
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OF: FRACTURE TREAT SHOOT OR ACIDIZE REFAIR WELL (Other)	PULL OR ALTER CAS MULTIPLE COMPLET ABANDON® CHANGE PLANS	FRACTURE TE SHOOTING OF (Other)	EATMENT ALTERING CABING
		Comple	tion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 4001'. Ran 99 jts. 7", 20.0#, K-55 intermediate casing, 3989' set 0 4001'. Cemented with 110 sks. Class"B" 65/358-27-85 Poz with 6% gel and 2% calcium chloride, 1/2 cu.ft. Perlite (212 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours, held 1200#/30 min. Top of cement @ 2300'.

9-1-85

TD 8076'. Ran 194 its. 4 1/2", 11.6# , K-55 casing, 8064's set 0 8076'. Float collar 0 8070'. Cemented with 235 sks. Class "B" with 8% gel, 12.5#/sk Gilsonite, 0.4 dispersant followed by 100 sks Class "B" with 0.5% dispersant, 0.2 gal/sk fluid loss additive and 0.3% retarder (total 594 cu.ft.) WOC 18 hours. Top of cement @ 3500'.



	Service No. 100 March 1914	
18. I hereby certify that the foregoing is true and correct significant land correct significant signi	Drilling Clerk	D ₁ 27 9-4-85
(This space for Federal or State office use) APPROVED BY	TITLE	AGCEPTED FOR REGORD
CONDITIONS OF APPROVAL, IF ANY:		,985

*See Instructions on Reverse Side

FARILINA JOH	NEGUUNGÉ	AREA
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		