

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | |
|---|---|
| 1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> | 7. UNIT AGREEMENT NAME San Juan 28-5 Unit |
| 2. NAME OF OPERATOR El Paso Natural Gas Company | 8. FARM OR LEASE NAME San Juan 28-5 Unit |
| 3. ADDRESS OF OPERATOR Post Office Box 4289, Farmington, NM 87499 | 9. WELL NO. 79E |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 800'N, 1163'E | 10. FIELD AND POOL, OR WILDCAT Basin Dakota |
| | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7, T-28-N, R-5-W N.M.P.M. |
| 14. PERMIT NO. OCT 25 1985 | 15. ELEVATIONS (Show whether DF, RT, CR, etc.) 6677'GL |
| | 12. COUNTY OR PARISH Rio Arriba |
| | 13. STATE NM |

RECEIVED

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data
BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

Spud Well

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10-23-85 Spudded well at 6:30 p.m. 10-23-85. Drilled to 227'. Ran 5 jts. 9 5/8", 32.3#, H-40 surface casing set at 223'. Cemented with 230 sks. Class "B", with 1/4# gel flake/sk, 3% calcium chloride, (271 cu.ft.). Circulated to surface. WOC 12 hours. Tested 600#/30 minutes, held ok.

OCT 30 1985
OIL
DIST.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Clerk

DATE

10-24-85

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side