5. LEASE

## UNITED STATES

DEPARTMENT OF THE INTERIOR	NM 010516
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
· · · · · · · · · · · · · · · · · · ·	
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	San Juan 28-5 Unit
	8. FARM OR LEASE NAME
1. oil gas de state de servicion de la contraction de la contracti	San Juan 28-5 Unit
2. NAME OF OPERATOR	9. WELL NO. 2.18 - 12A
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Blanco M.V.
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR
<ol><li>LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li></ol>	AREA Sec. 7, T-28-N, R-5-W
AT SURFACE: 1460'S, 1610'E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Rio Arriba New Mexico
	14. API NO. 25 4 3 5 5 5 5
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6664' GL 404.4
TEST WATER SHUT-OFF 🔲 💢	
FRACTURE TREAT	그는 이 시 및 그 역용회장 그 등 목품질빛
SHOOT OR ACIDIZE	(NOTE: Boost regular of multiple
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
MULTIPLE COMPLETE	그 그는 한 그 불빛성이 그 저는 욕심용을 보냈다.
CHANGE ZONES	그 그 그 선생들은 얼마 얼마 얼마 나를 느꼈다.
(other)	三十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二十二
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is discovered to the control of	e all pertinent details, and give pertinent dates, irectionally drilled, give subsurface locations and
including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen	t to this work.)*
r + ro - 0 - 11 1 - 11 - 11 1 C 1-1-	D- 5 14- 0 5 70H 176# 17 FF
5-4-79: Spudded well. Drilled surface hole.	Ran 5 jts. 9 5/8", 36#, K-55
surface casing, 208' set at 219'. Cemented w/224 cu. ft. cement. Circulated to surface. WOC 12 hours; held 600#/30 minutes.	
Circulated to Surface. Mod 12 hours, held oot with the contraction of	
,	
· ·	
	· · · · · · · · · · · · · · · · · · ·
Subsurface Safety Valve: Manu. and Type	Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED A. Busco TITLE Drilling Cle	rk DATE May 7, 1979
HILE	UNIE
(This space for Federal cr State offi	ce use)
APPROVED BY TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:	Sensity
	됐습으였은 첫 <b>의</b> 평원 <b>크린</b>
	naibal