

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. CENSUR ☐ Other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 4289, Farmington, NM 87499.

4. LOCATION OF WELL (Report location clearly and in accordance with instructions on reverse side)

At surface 990'S, 1555'E

At top prod. interval reported below

At total depth

RECEIVED

OCT 25 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

14. PERMIT NO.

SF 079250

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-5 Unit

8. FARM OR LEASE NAME

San Juan 28-5 Unit

9. WELL NO.

18A

10. FIELD AND POOL, OR WILDCAT

Blanco Mesa Verde

11. SEC. T. R. M., OR BLOCK AND SURVEY OR AREA

Sec. 11, T-28-N, R-5-W
NMPM

12. COUNTY OR PARISH

Rio Arriba

13. STATE

NM

15. DATE SPUDDED

9-20-85

16. DATE T.D. REACHED

9-29-85

17. DATE COMPL. (Ready to prod.)

10-23-85

18. ELEVATIONS (OF RKB, RT, GR, ETC.)*

7526' GL

19. ELEV. CASINGHEAD

7526'

20. TOTAL DEPTH, MD & TVD

7157'

21. PLUG. BACK T.D., MD & TVD

7143'

22. IF MULTIPLE COMPL., HOW MANY*

One

23. INTERVALS DRILLED BY

ROTARY TOOLS

Rotary

CABLE TOOLS

NO

24. PRODUCING INTERVAL(S). OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

6216-7059' (Blanco Mesa Verde)

25. WAS DIRECTIONAL SURVEY MADE

NO

26. TYPE ELECTRIC AND OTHER LOGS RUN

Comp. Density Dual Spaced NL; Temp Survey;
Comp. Analyzed Log; Ind. Log; Correlation GR-L; Comp. Density SNL; Temp. L

27. WAS WELL CORED

NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#	354'	12 1/4"	283 cu ft	
7"	20.0#	4879'	8 3/4"	609 cu ft	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	4716'	7157'	436 cu ft		2 3/8"	7046'	

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

Pressure test
to 3500 psi-ok. Perf'd 6760, 6763, 6780,
6792, 6802, 6809, 6825, 6829, 6839, 6880,
6895, 6899, 6912, 6921, 6925, 6929, 6972,
7029, 7055, 7059, w/20 SPZ. 2nd stage
6216, 6303, 6327, 6340, 6344, 6348, 6352,

32. ACID. SHOT. FRACTURE. CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
6760-7059'	64,500# 20/40 sand & 103,152 gals slickwater
6216-6722'	49,050# 20/40 sand & 109,136 gals slickwater

*Continued Perf's Listed on Back Pg. 1

PRODUCTION

DATE FIRST PRODUCTION 10-14-85
PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flowing - when connected.
WELL STATUS (Producing or shut-in) Shut in

DATE OF TEST 10-23-85
HOURS TESTED SI 7 Days
CHOKE SIZE 0
PROD'N. FOR TEST PERIOD
OIL—BBL. 0
GAS—MCF. 0
WATER—BBL. 0
GAS-OIL RATIO 0

FLOW. TUBING PRESS. SI 830
CASING PRESSURE SI 900
CALCULATED 24-HOUR RATE
OIL—BBL. No Flow
GAS—MCF. No Flow
WATER—BBL. No Flow
OIL GRAVITY-API (CORR.) 0

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Shut in to be Sold

TEST WITNESSED BY

John Easley

35. LIST OF ATTACHMENTS

Temp Survey

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Drilling Clerk

DATE

10-24-85

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37 SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Ojo Alamo	3810'	3958'	ss. White cr-grn s.	Ojo Alamo Kirtland Fruitland Pic.Cliffs Chacra Mesa Verde Point Lookout Mancos	3810'	
Kirtland	3958'	4183'	Gry sh interbedded w/tight gry fine-grn ss.		3958'	
Fruitland	4183'	4493'	Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss.		4183'	
Pictured Cliffs	4493'	5238'	Gry, fine-grn tight, varicolored soft ss.		4493'	
Chacra	5238'	6298'	Gry fn grn silty, glauconitic sd stone w/drk gry shale		5238'	
Mesa Verde	6298'	6366'	Gry, fine-grn, dense sil ss., carb sh & coal	Mancos	6298'	
Menefee	6366'	6662'	Gry, fine-grn s, carb sh & coal		6366'	
Point Lookout	6662'	7152'	Gry, very fine sil ss w/frequent sh breaks		6662'	
Mancos	7152'	7157'	Gry carb sh.		7152'	
* Continued Perf s:						
6356, 6360	6364, 6509	6514, 6544	6672, 6676, 6680, 6684, 6704, 6708, 6719, 6720, 6721, 6722, w/23 SPZ.			