• • • • • • •	UNITED STATES PARTMENT OF THE IN	NTERIOR (Other Instructions o	
SUNDRY	NOTICES AND REPO		G. IF INDIAN, ALLOTTES OR TRIBE NAME
Use "A	PPLICATION FOR PERMIT—" fo	or such propossis.)	Jicarilla Apache Tribe
04L 🗔 6A8 🔯	THEE		
NAME OF OPERATOR			8. PARM OR LEASE NAMES
Mallon Oil Comp	oany c/o KM Producti		Jicarilla 480 9. WHILE NO.
P.O. Box 2406,	Farmington, NM 874	199 RECEIVED	1
LOCATION OF WELL (Report loc See also space 17 below.) At surface	ation clearly and in accordance w	MAY 1.9 1987	Undes. Gallup/Basin Dako
2310' FSL & 20	000' FWL	BUREAU OF LAND MANAGEMEN	11. SEC., T., E., M., OR BLE, AND SURVEY OR ARMA
		FARMINGTON RESOURCE AREA	Sec. 21, T28N, R1W
PERMIT NO.	15. ELEVATIONS (Show what 7255 '		RIO Arriba NM
Che	ck Appropriate Box To Indi	icate Nature of Notice, Report,	or Other Data
NOTICE OF	INTENTION TO:		DESIGNET REPORT OF:
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
PRACTUSE TREAT	MULTIPLE COMPLETE	- FEACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZA	ABANDON*	SHOOTING OR ACIDIZING (Other) Spud & S	
			MITAGE CEMENTE
spud well at 3:	directionally drilled, give subsurfa	(Norm: Report re Completion or Respectivent details, and give pertinent date locations and measured and true v	suits of multiple completion on Well completion Report and Log form.) area, including estimated date of starting any certical depths for all markers and sones perti-
Other) DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.) Spud well at 3: 2 hours do to t and set 270 ft (207 ft) of Cl	15 p.m. 5/18/87 - Dright hole - Ran 6 jr RKB - Rigged up Ceme. ass B cement with 25	(Norm: Report re Completion or Re- pertinent details, and give pertinent d ace locations and measured and true v	atea, including estimated date of starting any ertical depths for all markers and somes perticipated by the surface hole - Circulate is new surface casing surface with 175 sx sion throughout job -
DESCRIBE PROPOSED OR COMPLET proposed work. If well is nent to this work.) Spud well at 3: 2 hours do to t and set 270 ft (207 ft) of Cl	15 p.m. 5/18/87 - Dright hole - Ran 6 jr RKB - Rigged up Ceme. ass B cement with 25	(Norm: Report re Completion or Reportinent details, and give pertinent date locations and measured and true variable 275 feet of 12% ts of 9 5/8" 36#/ft J-5 enters, Inc Cemented & CaCl - good circulate	atea, including estimated date of starting any ertical depths for all markers and somes perticipated by the surface hole - Circulate is new surface casing surface with 175 sx sion throughout job -
DESCRIBE PROPUSED OR COMPLET proposed work. If well is nent to this work.) Spud well at 3: 2 hours do to t and set 270 ft (207 ft) of Cl circulated ceme	TITLE	(Norm: Report re Completion or Reportinent details, and give pertinent dece locations and measured and true virilled 275 feet of 12½ ts of 9 5/8" 36#/ft J-5 enters, Inc Cemented % CaCl - good circulate plug down at 12:30 a.m	ates, including estimated date of starting any ertical depths for all markers and somes perticipated by surface hole - Circulate is new surface casing surface with 175 sx sion throughout job - 1. 5/19/87 - WOC
DESCRIBE PROPUSED OR COMPLET proposed work. If well is nent to this work.) Spud well at 3: 2 hours do to t and set 270 ft (207 ft) of Cl circulated ceme	TITLE	(Norm: Report re Completion or Reportinent details, and give pertinent dece locations and measured and true virilled 275 feet of 12½ ts of 9 5/8" 36#/ft J-5 enters, Inc Cemented % CaCl - good circulate plug down at 12:30 a.m	atea, including estimated date of starting any ertical depths for all markers and somes perticipated by the surface hole - Circulate is new surface casing surface with 175 sx sion throughout job - 1. 5/19/87 - WOC

*See Instructions on Reverse Side