UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS								
1. 2	TYPE OF WELL GAS	DECT 7 1990 OIL CON. DIV.7		LEASE NU SF-08 IF INDIA	0430	OR TRIB	E NAME	
2.				7. UNIT AGREEMENT NAME SAN JUAN 28-6 UNIT				
3.				8. FARM OR LEASE NAME SAN JUAN 28-6 UNIT 9. WELL NO. 414				
4.	LOCATION OF WEI 1465'FSL 1250		ļ	FIELD, PO BASIN SEC. T. SEC.	FRUI R. M OR	TLAND C	•	
14.	PERMIT NO. 30-039-24961	15. ELEVATIONS 6818'GL	12.	COUNTY RIO ARR	1	STATE NM		
16.	SUBSEQUENT REPO	ORT OF:						
17. Describe proposed or completed operations SPUD DATE: 110190 SPUD TIME: 1600 TD 232', ran 5 jts of 8 5/8" 24.0# K-55 casing, 209' set @ 222'. Cemented with 210 sacks of Class B cement with 1/4# Flocele/sack and 3% calcium								
chloride (242 cu ft.). Circulated 12 bbls to surface. WOC 12 hours. Pressure tested to 800 psi for 30 minutes. Held OK.								
DATE: 110790								
TD 3638', ran 87 jts of 5 1/2" 15.5# K-55 casing, 3623' set @ 3636'. Stage tool set @ 2942', insert baffle @ 3550', float collar @ 3590', and cement nose guide shoe @ 3636'. Stage 1. Lead with 50 sacks of Class G cement 65/35 Poz, 6% gel, 2% calcium chloride, 5# gilsonite/sack, and 1/4# Flocele/sack, (89 cu ft.). Tail with 100 sacks of Class G cement with 2% calcium chloride, (118 cu ft.). Circulated a trace of cement to surface. Stage 2. Lead with 540 sacks of Class G cement with 65/35 Poz, 6% gel, 2% calcium chloride, 5# gilsonite/sack, and 1/4# Flocele/sack, (956 cu ft.). Tail with 60 sacks of Class G cement with 2% calcium-chloride, (70 cu ft.). Circulated 12 bbls to surface. WOC 18 hours.								
18.	AUTHORIZED BY	REGULATORY AFFAIRS	eld			7-/3-90 ATE	2	
NOTE: THIS FORMAT IS ISSUED IN LIEU OF US BLM FORM 3160-5.								
(This space for Federal or State office use)								
APPROVED BY TITLE_					DATE FARM	NGTON RESOLU	RCE AREA	