UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

| | SUNDRY NOTICES AND RE | PORTS ON WELLS |
|---|---|---|
| 1. TYPE OF WELL GAS | OIL CON. DIV. | 5. LEASE NUMBER SF-079193 6. IF INDIAN, ALL. OR TRIBE NAME |
| | DIST. 3 | 7. UNIT AGREEMENT NAME SAN JUAN 28-6 UNIT |
| 3. ADDRESS & PHONE P O BOX 4289 FARMINGTON, | NO. OF OPERATOR | 8. FARM OR LEASE NAME SAN JUAN 28-6 UNIT 9. WELL NO. 457 |
| 4. LOCATION OF WEI 820'FNL 1520' | | 10. FIELD, POOL, OR WILDCAT BASIN FRUITLAND COAL 11. SEC. T. R. M OR BLK. SEC. 20 T28N R06W NMPM |
| 14. PERMIT NO. 30-039-24997 | 15. ELEVATIONS 6518'GL | 12. COUNTY 13. STATE RIO ARRIBA NM |
| 16. SUBSEQUENT REPO | ORT OF: SPUD | |
| SPUD DATE: 110790 TD 236'. Ran 5 j with 210 sacks of (248 cu ft.). Ci to 600 psi for 30 DATE: 111290 TD 3302'. Ran 77 tool set @ 2649', cement nose guide G 65/35 Poz, 6% g (132 cu ft.). Ta (115 cu ft.). Ci of Class G 65/35 Flocele/sack, (85 | rculated 13 bbls to surfation in the surfation of 5 1/2" 15.5# K-55 insert baffle @ 3214', at shoe @ 3302'. First statel, 2% calcium chloride, il with 100 sacks of Clastroulated 4 bbls to surface Poz, 6% gel, 2% calcium chloride. | casing, 221' set @ 234'. Cemented calcium chloride and 1/4# Flocele/sack ace. WOC 12 hours. Pressure tested 5 casing, 3289' set @ 3302'. Stage auto fill float collar @ 3257', and age cement with 75 sacks of Class 5# gilsonite/sack, and 1/4# Flocele/sack as G cement with 2% calcium chloride ce. Second stage cement with 480 sacks chloride, 5# gilsonite/sack and 1/4# sacks of Class G cement with 2% |
| 18. AUTHORIZED BY: | REGULATORY AFFAIRS | |
| | ======================================= | IS BLM FORM 31ACOEPTED FOR RECORD |
| (This space for Fede | ral or State office u | |
| APPROVED BY CONDITION OF APPROVA | TITLE_ | FARMINGTON RESOURCE AREA |