

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

5F-078497

6. If Indian, Alutian or Tribe Name

7. Unit or Pool, or Agreement Designation

8. Well Name and No.

San Juan 28-7 "238R

8. API Well No.

30-039-25336

10. Field and Pool, or Exploratory Area

Basin Dakota

11. County or Parish, State

Rio Arriba, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

D. Tallant

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

(303) 830-4040

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1500' FSL, 1640' FWL

Section

29

Township

28N

Range

7W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMITTAL

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud & Set

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 17.5" surface hole on 11-5-93 at 2:30 hrs. Drilled to 428'.

Set 13.375" 4.8# K-55 surface casing at 428'. Cemented with 500 SX CLB. Circulated 40 BBLs to the surface.

Pressure tested casing to 1000 psi. Drilled a 12.25" hole to a depth of 3210' on 11-11-93. Set 9.625" 36# K-55 intermediate

casing at 3210'. Cemented with 1st Stg-370 SX CLB, 2nd Stg-580 SX CLB, Tail w/100 SX CLB. Circulated 25 BBLs to the surface. Pressure tested casing to 1500 psi.

Drilled a 8.750" hole to a depth of 6840' on 11-17-93. Set 7", 23#, J-55 protective casing at 6840'. Cemented with 825 SX 50/50 POZ CLB. TOC @ 2650'.

Drilled a 6.250" hole to a TD depth of 7453' on 11-27-93. Set 4.5", 11.1#, N-80 Production Liner, Top at 6649', Bottom at 7453' cemented with 120 SX CLB. TOC @ 6649'.

Rig released at 10:00 hrs. on 11-27-93.

14. I hereby certify that the foregoing is true and correct

Signed

DeAnne Tallant

Title

Staff Asst.

Date

1-5-94

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

FILED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

\* See Instructions on Reverse Side

BY

FARMINGTON DISTRICT OFFICE

Sm