

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT" for such proposals

RECEIVED
MAR 31 1994

RECEIVED
BLM

5. Lease Designation and Serial No.

SE - 078498

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

San Juan 28-7 #193M

9. API Well No.

30-039-25337

10. Field and Pool, or Exploratory Area Basin
Blanco Mesaverde/ Dakota

11. County or Parish, State

Rio Arriba, New Mexico

1. Type of Well

Oil Well Gas Well Other

OIL CON. DIV.
DIST. 3

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

D. Tallant

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

(303)830-5427

4. Location of Well (Footage, Sec., T., R., M. or Survey Description)

800' FNL, 1040' FWL

Section 28 Township 28N Range 7W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- Notice of Intent
- Subsequent Report
- Final Abandonment Notice

- Abandonment
- Recompletion
- Plugging Back
- Casing Repair
- Altering Casing
- Other Spud & Set

- Change of Plans
- New Construction
- Non-Routine Fracturing
- Water Shut-Off
- Conversion to Injection
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 14.75" surface hole on 2/22/94 at 08:00 hrs. Drilled to 405'

Set 11.75" 42# H-40 surface casing at 400'. Cemented with 300 SX CL B CMT. Circulated 29.5 BBLS to the surface.

Pressure tested casing to 500 psi. Drilled a 10-5/8" hole to a depth of 3050' on 2/28/94. Set 8-5/8" 32# J-55 intermediate casing at 3050'. Cemented with 1st Stg-220 SX CL B, 2nd Stg -430 SX CL B, Tail w/100 SX CL B. Circulated 20 BBLS to the surface. Pressure tested casing to 2000 psi.

Drilled a 7.875" hole to a TD depth of 7282' on 3/5/94 Set 5.5", 15.5#, K-55 Production Liner, Top at 2400', Bottom at 7282' cemented with 900 SX 50/50 CL B/POZ "A" TOC @ 2400'.

Rig released at 08:00 hrs. on 3/5/94.

14. I hereby certify that the foregoing is true and correct

Signed Dianne Tallant

Title Staff Assistant

Date 03/21/94

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

ACCEPTED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

MAR 25 1994

* See Instructions on Reverse Side

FARMINGTON DISTRICT OFFICE

RV

Samm