

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-079289A

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

San Juan 28-7 Unit #414

9. API Well No.

3003925048

10. Field and Pool, or Exploratory Area

11. County or Parish, State

Rio Arriba, New Mexico

1. Type of Well

☐ Oil Well

☒ Gas Well

☒ Other

Nitrogen Injection

2. Name of Operator

Amoco Production Company

Attention:

Julie L. Acevedo

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

910FSL 820 FWL

Section

14

Township

28N

Range

7W

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐

Abandonment

☐

Recompletion

☐

Plugging Back

☐

Casing Repair

☐

Altering Casing

☒

Other Spud & Set

☐

Change of Plans

☐

New Construction

☐

Non-Routine Fracturing

☐

Water Shut-Off

☐

Conversion to Injection

☐

Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 12.25" surface hole on 11/26/94 at 16:00 hrs. Drilled to 269'.

Set 8.625" 24# J-55 surface casing at 268'. Cemented with

180sx C1 B. Circulated 3 BBLs to the surface.

Pressure tested casing to 1500 psi. Drilled a 7.875" hole to a TD

of 3375' on 12/2/94 Set 5.5" 17# N-80 production

casing at 3375'. Cemented with 450sx C1B, tail w 110sx C1 B, pump 100sx C1 B Cmt Cap.

Circulated 10 BBLs good cement to the surface. Rig released at 0300 hrs. on 12/2/94.

14. I hereby certify that the foregoing is true and correct

Signed

Julie L. Acevedo

Title

Sr. Staff Assistant

Date 12/13/94

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

ACCEPTED FOR RECORD

Date

DEC 13 1994