

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

SE-080516B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 28-5 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 28-5 Unit #211

9. API WELL NO.

30-039-25362

10. FIELD AND POOL OR WILDCAT
Tapacito Pictured Cliffs
Basin Fruitland Coal

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec.13, T-28-N, R-5-W

12. COUNTY OR
PARISH
Rio Arriba

13. STATE
NM

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐ 21 SEP 20 21 3:35

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. CENVR. ☐ Other ☐ 070 011 104, 111

2. NAME OF OPERATOR

Meridian Oil Inc

3. ADDRESS AND TELEPHONE NO.

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface

1715' FSL, 1545' FWL

At top prod. interval reported below

At total depth

DHC-1003

14. PERMIT NO.

DATE ISSUED

15. DATE SPUDDED 7-2-94 16. DATE T.D. REACHED 7-10-94 17. DATE COMPL. (Ready to prod.) 8-26-94 18. ELEVATIONS (CF, RKB, RT, GR, ETC.)* 7531 GR 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 4665 21. PLUG. BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., HOW MANY? 2 23. INTERVALS DRILLED BY 0 4665 24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 4362-4458 Fruitland Coal DHC w/Pictured Cliffs 25. WAS DIRECTIONAL SURVEY MADE

26. TYPE ELECTRIC AND OTHER LOGS RUN

HRL, Ind-GR, 4-Arm CAL

27. WAS WELL CORED

No

29. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
8 5/8	24#	547	12 1/4	454 cu.ft.	
4 1/2	10.5#	4635	7 7/8	1782 cu.ft.	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8	4552	

31. PERFORATION RECORD (Interval, size and number)

4362-4458

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4362-4458	60,000# 20/40 Ariz sd
	6006 gal 30# x-link gel

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
8-26-94		Flowing				SI	
DATE OF TEST	HOURS TESTED	CHOKER SIZE	PROD'N. FOR TEST PERIOD	OIL—BSL.	GAS—MCF.	WATER—BSL.	GAS-OIL RATIO
8-26-94			—————→		77 Pitot Gauge		
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BSL.	GAS—MCF.	WATER—BSL.	OIL GRAVITY-API (CORR.)	
	SI 1035	—————→					

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.

ACCEPTED FOR RECORD

SIGNED

[Signature]

TITLE

Regulatory Affairs

DATE 9-29-94

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any Federal official or officer of the United States any false, fictitious or fraudulent statements or representations as to any matter within the jurisdiction of the Federal Government.

BY

RECEIVED DISTRICT OFFICE
OCT 04 1994
[Signature]

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH

38.

GEOLOGIC MARKERS

Ojo Alamo	3904'	3983'	White, cr-gr ss.	Ojo Alamo	3904'	
Kirtland	3983'	4100'	gry sh interbedded w/tight, gry, fine gr ss.	Kirtland	3983'	
Fruitland	4100'	4470'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	4100'	
Pictured Cliffs	4470'	4665'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	4470'	