Form 3160-5 ((June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BURE (U) OF LAND MANAGEMENT

BEDETYSO	
- 17	
المحاجين الراوان	

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BURE	U/OF LAND MANAGEMENT	Expired: William 31, 1993	
CHNDDA NO	TICES AND REPORTS ON WELLS", 12 Mgs	5. Lease Designation and Serial No.	
	5P=U/64 /=A		
Use "APPLIC	ATION FOR PERMIT - " for such proposals) / Francisco VIV. N	6. If Indian, Allottee or Tribe Name	
	DECEIVEN		
		7. If Unit or CA, Agreement Designation	
1. Type of Well	39L 1 8 1994 Act		
Oil XX Gas Other	OUL CORL DAY	B. Wall Name and No.	
2. Name of Operator	ANY DUMES Tulie Acevedo	San Juan 28-7 Unit #220M	
ATOO I ROBOTION COLLANT COLLANT			
3. Address and Telephone No. P.O. Box 800 Denver, Colorado	30-039-25398 10. Field and Pool, or Exploratory Area Blanco		
4. Location of Well (Footage, Sec., T., R., M., or	Basin Dakota/ Mesaverde		
1490 FNL 1800 FWL	Section 22 Township 28N Range 7W	11. County or Parish, State	
		Rio Arriba, New Mexico	
12. CHECK APPROPR	IATE BOX(s) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACTION		
	· · · · · · · · · · · · · · · · · · ·		
Notice of Intent	Abendonment Recompletion	Change of Plans New Construction	
Subsequent Report	Plugging Beck	Non-Routine Frecturing	
AM3 Subsequent Neport	Casing Repair Attering Casing	Water Shut-Off Conversion to Injection	
Final Abandonment Notice	KX other _ Spud & Set	Dispose Water	
		ort results of multiple completion on Well Completion or on Report and Log form.]	
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work . If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			
Spud a 14.75" surface hole on 5/22/94 at 19:15 hrs. Drilled to 430			
Set 11.75" 47# J-55 surface casing at 430 '. Cemented with			
220 sx C1 B Circulated 5 BBLS to the surface.			
Pressure tested casing to 2,000 psi. Drilled a 10.625 "hole to a depth of			
3833 'on 5/28/94. Set 8.625" 24# & 32# J-55 Intermediate 1st stg 260 sx Cl B, 2nd stg 600 sx Cl B, tail w/100 sx Cl B			
casing at 3833 ' Cemented with Dy @ 3084'.			
Circulated 60 BBLS to the surface. Pressure tested casing to 2500 psl.			
Drilled a " ho	le to a depth of $8020'$ on $6/4/94$. Set 5.5, 1	7#, N-80 Production	
casing at 8020' . Cemented with 1st stg 665, 50/50 poz, tail 200 sx Cl B, DV @ 4593'.			
.	• .		
		10.00	
•	Rig released at .	12:00 hrs. on 6/3/94.	
14. I hereby certify that the foregoing is true and correct			
Signed And Lac	Title	Date	
(This space for Federal or State office use)			
V		JOLL ALL FOR RECORD	
Approved by	Title	1111 1 10 100A	