

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

ENPE CORPORATION

3. Address and Telephone No.

P. O. BOX 6027  
SAN ANTONIO, TEXAS 78209

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1950' FUL & 1800' FEL  
Sec 22 T28N, R1W NMPM.

5. Lease Designation and Serial No.

701-94-0012

6. If Indian, Allottee or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cedar Canyon 22G #1

9. API Well No.

30-039-25471

10. Field and Pool, or Exploratory Area

Boulder Mancos

11. County or Parish, State

Rio Arriba NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/26/94 6pm Spud well. Drill 13 3/4" hole to 365' RAN 8 jts 10 3/4" 40.5"  
K-SS ST&C Rg-III csg to 324' KB. Halliburton cementation w/ 310 SX  
class 'B' w/ 2% CaCl<sub>2</sub>, 3% NaCl, 1/4#/sk Cellaphane. Plug down @ 6:45 am 9/27/94.

10/13/94 Drilled 8 3/4" hole to 5694. RAN HOWCO DILL, GR, Long Spaced Sonic, GR/CO,  
DSN Logs. LAST survey @ 5655' MD, 3° Vert. Deviation, N 43.7° W, BHL 130' East  
113' North of surface location. Plug back w/ 90sx class 'G' cmt w/ 35% silica sand,  
1% CaCl<sub>2</sub>, 1/2% CRR-3 from 5294' to 5100'. PBD survey @ 5028' MD, 3 1/2° Dev,  
N 52.3° E, BHL 146' E & 83' N

10/22/94 Drilled to 6668' MD w/ 8 3/4" bit. RAN 7" 23# N & K LTC Rg III csg to 6668' MD  
LAST survey 6613' MD, 47.7° Dev, S 72.10° W, BHL 30.16' S & 403.92' W of surface location.

10/28/94 Drill 6 1/4" hole to 7396' MD. LAST survey: 7341' MD, 6738' TVD, 75.60°, BHL 255' S &  
1021' W of surface location.

12/14/94 (CONTINUED ON ATTACHED PAGES)

14. I hereby certify that the foregoing is true and correct

Signed

Title

Date

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Chief, Lands and Mineral Resources

DEC 19 1994