

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

COPY

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT-" for such proposals.

SUBMIT IN TRIPLICATE

5. LEASE DESIGNATION AND SERIAL NO

SF-079294

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. IF UNIT OR CA. AGREEMENT DESIGNATION

San Juan 28-7 Unit

8. WELL NAME AND NO

#226M

9. API WELL NO.

30-039-25694

10. FIELD AND POOL OR EXPLORATORY AREA

BLANCO MV/BASIN DAKOTA

11. COUNTY OR PARISH, STATE

RIO ARRIBA, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other: spud, cement & casing report

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8/11/97 Spudded well. Drilled surface hole. Ran 5 joints 9-5/8", 36#, 8rd ST & C, K-55 casing. Landed at 288. Cement with 215 sks. Class B cement with 3% CaCl₂ and .25 lb/sk Cello Flake. Displaced 18.9 bbls of H₂O. Cement returns 8-1/2 bbls. Floats held. Bumped held at 02:00 a.m. on 8/11/97 with 250 psi.

8/12/97 Pressure tested BOP's, 250# low for 10 minutes/2000# on high for 30 minutes. TIH. Drill cement and shoe.

8/14/97 Ran 106 joints 7", 23# K-55, ST & C, 8rd, casing, landed @ 3179'. Cement with 440 sks of 35/65 POZ, Class B w/ 8% Gel, 2% CaCl₂ .25#/sk Cello Flake, 6.25#/sk Gilsonite. Followed by 115 sks of Class B w/ 2% CaCl₂ .25#/sk Cello Flake. Displaced with 124.1 bbls of H₂O with full mud returns. Floats held. Bumped plug at 5:30 a.m. on 8/14/97 with 2000 psi. Had full returns throughout job. Circ 19 bbls of cement.

8/18/97 Ran 32 joints 4-1/2", 11.60#, K-55, 8rd LT&C casing. Ran 132 joints 4-1/2" 10.50#, K-55, 8rd ST&C casing. Landed at 7304'. Cement with 400 sks of 50/50 POZ Class B w/ 4% Gel, 2% KCL, 300% FL-52, 300% CD-32, 6.25lb/sk Gilsonite, .25lb/sk Cello Flake. Followed by 105 sks of Class H w/ 750% FL-62, 250% SM, 200% CD-32. Displaced with 115 bbls of water with partial mud return. No cement return. Floats held. Bumped plug at 7:00 a.m. on 8/18/97 with 2300 psi. Circ back 6 bbls of water.

8/19/97 ND. BOP, set slips w/ 62K make rough cut. Install hole cover, release rig @ 9:00 a.m. on 8/18/97.

14. I hereby certify that the foregoing is true and correct

SIGNED

Eric J. Giles For D. Bemenderfer

DEBRA BEMENDERFER

TITLE AGENT FOR CONOCO INC.

DATE 8/25/97

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

Conditions of approval, if any:

ACCEPTED FOR RECORD

AUG 27 1997

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON DISTRICT OFFICE
BY *[Signature]*

NMCCD