

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

9. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

L 1600' FSL, 255' FWL, Sec. 12, T-28-N, R-5-W, NMPM

NSL-4046

5. Lease Number
SF-079250

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

San Juan 28-5 Unit

Well Name & Number

San Juan 28-5 U #107

API Well No.

30-039-25931

10. Field and Pool

Blanco Mesaverde

11. County and State

Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - Spud

13. Describe Proposed or Completed Operations

9-12-98 MIRU. Spud well @ 5:00 p.m. 9-12-98. Drill to 254'. Circ hole clean. TOOH. TIH w/5 jts 9 5/8" 32.3# H-40 ST&C csg, set @ 250'. Cmdt w/200 sx Class "B" neat cmt w/3% calcium chloride, 0.5 pps Flocele (236 cu.ft.). Circ 17.5 bbl cmt to surface. WOC. NU BOP.

9-13-98 PT BOP & csg to 600 psi/30 min, OK. Drilling ahead.

9-17-98 Drill to intermediate TD @ 4548'. Circ hole clean. TOOH. TIH w/109 jts 7" 20# J-55 ST&C csg, set @ 4545'. Cmdt first stage w/200 sx Class "B" neat cmt w/3% Econolite, 10 pps Gilsonite, 0.5 pps Flocele (200 cu.ft.). Tailed w/90 sx Class "B" 50/50 poz w/2% gel, 10 pps Gilsonite, 0.5 pps Flocele, 2% calcium chloride (127 cu.ft.). Circ 9 bbl cmt to surface. WOC. Stage tool set @ 2257'. Cmdt second stage w/235 sx Class "B" neat cmt w/3% Econolite, 10 pps Gilsonite, 0.5 pps Flocele (684 cu.ft.). Circ 6 bbl cmt to surface. WOC.

9-18-98 WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

9-20-98 Drill to TD @ 6936'. Circ hole clean. TOOH. TIH w/59 jts 4 1/2" 10.5# J-55 ST&C lnr, set @ 6935'. Top of lnr @ 4378'. Cmdt w/295 sx Class "B" neat cmt w/2% gel, 5 pps Gilsonite, 0.25 pps Flocele, 0.4% fluid loss, 0.1% retardant (389 cu.ft.). Displace w/124 bbl wtr. Lost circ 117 bbl into displacement. No circ to surface. WOC. ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 9/21/98

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD

SEP 30 1998

FARMINGTON DISTRICT OFFICE

BY [Signature]

NMOC