Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

	BUREAU OF LAND MANAG	EMENT ((()))	5. LEASE DESIGNATION AND SERIAL NO. SF 079290-A	
SUNDRY NOTICES AND REPORTS ON		PORTS ON WELLS 10 11 9: 03	6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
	Do not use this form for proposals to drill or to deepen or reently to a different reservoir.			
	Use "APPLICATION FOR PERMIT-" for such proposals			
	TV DO		7. IF UNIT OR CA, AGREEMENT DESIGNATION	
L	SUBMIT IN TRIPLICATE		San Juan 28-7 Unit	
1.	TYPE OF WELL		8. WELL NAME AND NO.	
	OIL WELL GAS WELL OTHER	JAN coor	#186M	
2.	NAME OF OPERATOR		9. API WELL NO.	
	CONOCO INC.		30-039-26095	
3.	ADDRESS AND TELEPHONE NO.		10. FIELD AND POOL, OR EXPLORATORY AREA	
_	P.O. Box 2197, DU 3066, Houston, TX 77252-2197 (281) 293-1613		Blanco MV/Basin Dakota	
4.	LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Desc		11. COUNTY OR PARISH, STATE	
	2095' FNL & 1940' FWL, Unit Letter '		Rio Arriba County, NM	
12.	12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
	TYPE OF SUBMISSION TYPE OF ACTION			
	Notice of Intent	Abandonment	Change of Plans	
	Subsequent Report	Recompletion	New Construction	
	Z oubsequent report	Plugging Back	Non-Routine Fracturing	
	Final Abandonment Notice	Casing Repair	Water Shut-Off	
		Altering Casing	=	
		K=-71	Conversion to Injection	
		Other: Casing Report	Dispose Water (Note: Report results of multiple completion on Well Completion or	
13.	Recompletion Report and Log Form.)			
	directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)			
	<u>9/17/00</u> Well spudded.			
	9/18/00 Drilled surface hole. Ran 6 joints, 9-5/8" set at 289.5', hole size 12-1/4", 36#, J-55, ST&C casing. Cement with 144 sk Type III + 2% CaCl2 + 0.25 lb/sk Cello Flake. Displaced with 19 bbls of fresh water. Circulated 10 bbls to surface. Floats held. Bumped plug at 2:05pm with 500 psi.			
	9/25/00 Ran 91 joints, 7" set at 3755', hole size 8-3/4", 20#, J-55, ST&C casing. Cement with 461 sx Prem Lite + 2% CaCl2 + 0.25 lb/sk Cello Flake. Followed by 60 sx Type III + 2% CaCl2 + 0.25 lb/sk Cello Flake. Displaced with 148.5 bbls of fresh water, partial returns to surface. Floats held. Bumped plug at 3:50am with 1380 psi.			
	9/30/00 Ran 186 joints, 4-1/2" set at 7951', hole size 6-1/4", 10.5#, J-55, ST&C casing. Cement with 516 sx Prem Lite + 0.25 lb/sk Cello Flake + 0.2% CD-32 + 0.65% FL-52. Displace with 125.5 bbls of fresh water with no returns to surface. Floats held. Bumped plug at 2:50pm with 1120 psi.			
14.	! hereby certify that the foregoing is true and correct			
	SIGNED JUNIO TITLE DEBRA SITTNER, As Agent for ConocoAGC FOATED FORORECOF			
NOV 2 7 2			NOV 2 7 2000	
APPROVED BY		TITLE	DATE	
	Conditions of approval, if any:		FAHMINGTON FULL OFFICE	
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Unites States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction				