

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
BLM

Sundry Notices and Reports on Wells

JUL 15 PM 2:05
OIL CON. DIV.
DIST. 3
FARMINGTON, NM

1. Type of Well
GAS

2. Name of Operator
BURLINGTON RESOURCES OIL & GAS COMPANY

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1690' FSL, 1610' FEL, Sec.28, T-28-N, R-4-W, NMMP

7. Unit Agreement Name

8. Well Name & Number
Valdez #8A

9. API Well No.
30-039-26141

10. Field and Pool
Blanco Mesaverde

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging Back
	<input type="checkbox"/> Casing Repair
	<input type="checkbox"/> Altering Casing
	<input checked="" type="checkbox"/> Other -
	<input type="checkbox"/> Change of Plans
	<input type="checkbox"/> New Construction
	<input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Conversion to Injection

13. Describe Proposed or Completed Operations

7-8-99 Drill to intermediate TD @ 3858'. Circ hole clean. TOOH. TIH w/87 jts 7" J-55 20# ST&C csg, 5 jts 7" 23# N-80 csg, set @ 3849'.

7-9-99 Pump 20 bbl wtr, 20 bbl mud flush, 20 bbl wtr ahead. Cmtd w/350 sx Class "B" 50/50 poz w/3% Econolite, 0.25 pps Flocele, 10 pps Gilsonite (1019 cu.ft.). Tailed w/90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 0.25 pps Flocele, 10 pps Gilsonite (127 cu.ft.). Displace w/151 bbl wtr. Circ 60 bbl cmt to surface. WOC. PT BOP & csg to 1500 psi/30 min, OK. Drilling ahead.

7-11-99 Drill to TD @ 6751'. Circ hole clean. TOOH. TIH w/73 jts 4 1/2" 11.6# K-55 LT&C lnr, set @ 6750'. Top of lnr @ 3709'. Pump 10 bbl wtr, 20 bbl mud flush, 10 bbl wtr ahead. Cmtd w/365 sx Class "B" 50/50 poz w/2% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.4% fluid loss, 0.1% retardant, 0.2% CFR3 (481 cu.ft.). Displace w/73 bbl wtr. Reverse circ 10 bbl cmt to surface. WOC. PT csg to 3000 psi/15 min, OK.

7-12-99 ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 7/15/99

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

ACCEPTED FOR RECORD
JUL 20 1999
FARMINGTON FIELD OFFICE
BY [Signature]