

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

## 1. Type of Well

GAS

## 2. Name of Operator

**BURLINGTON  
RESOURCES**

OIL &amp; GAS COMPANY

## 3. Address &amp; Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

## 4. Location of Well, Footage, Sec., T, R, M

2305' FNL, 75' FWL, Sec. 32, T-28-N, R-4-W, NMPM

## 5. Lease Number

SF-079731

6. If Indian, All. or  
Tribe Name

## 7. Unit Agreement Name

San Juan 28-4 Unit

## 8. Well Name &amp; Number

San Juan 28-4 U #5C

## 9. API Well No.

30-039-26288

## 10. Field and Pool

Blanco Mesaverde

## 11. County and State

Rio Arriba Co, NM

## 12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

## Type of Submission

## Type of Action

☒ Notice of Intent☐ Abandonment☒ Change of Plans☐ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging Back☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☒ Altering Casing☐ Conversion to Injection☐ Other -

## 13. Describe Proposed or Completed Operations

It is intended to alter the approved casing depths and cement of the subject well.

## Revisions:

## Mud Program:

| Interval   | Type     | Weight  | Fluid Loss |
|------------|----------|---------|------------|
| 200-3920'  | LSND     | 8.4-9.0 | No control |
| 3920-6776' | Air/Mist | n/a     | n/a        |

## Casing Program:

| Hole Size | Depth Interval | Casing Size | Weight | Grade |
|-----------|----------------|-------------|--------|-------|
| 8 3/4"    | 0-3920'        | 7"          | 20.0#  | J-55  |
| 6 1/4"    | 3820-6776'     | 4 1/2"      | 10.5#  | J-55  |

## Cementing Program:

7" intermediate casing - lead w/363 sx Class "B" cement with 3% sodium metasilicate, 7 pps Gilsonite, 0.5 pps Flocele. Tail with 90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 7 pps Gilsonite, 0.5 pps Flocele (1179 cu.ft. of slurry, 100% excess to circulate to surface).

4 1/2" production liner - cement with 301 sx Class "B" 50/50 poz w/2% gel, 0.25 pps Flocele, 5 pps Gilsonite, 0.4% fluid loss, 0.1% retardant (425 cu.ft., 50% excess to circulate liner).

## 14. I hereby certify that the foregoing is true and correct.

Signed Nancy Oltmanns - for Title Regulatory Supervisor Date 7/11/00  
no

(This space for Federal or State Office use)

APPROVED BY /s/ Jim Lovato Title \_\_\_\_\_ Date JUL 12 2000

CONDITION OF APPROVAL, if any: