

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1980' FNL, 1860' FWL, Sec. 23, T-28-N, R-6-W, NMPM, Rio Arriba County

API # (assigned by OCD)
30-039-26619

5. Lease Number
Fee

6. State Oil & Gas Lease #

7. Lease Name/Unit Name

San Juan 28-6 Unit

8. Well No.
107M

9. Pool Name or Wildcat
Blanco MV/Basin DK

10. Elevation:

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other -

13. Describe Proposed or Completed Operations

2-28-01 Drill to intermediate TD @ 3555'. Circ hole clean.

3-1-01 TOOH. TIH w/85 jts 7" 20# J-55 ST&C csg, set @ 3550'. Pump 20 bbl wtr, 20 bbl mud, 20 bbl wtr ahead. Cmdt w/440 sx Class "B" 50/50 poz w/4% gel, 4% calcium chloride (1105 cu.ft.). Tailed w/90 sx Class "B" 50/50 poz w/2% gel, 2% calcium chloride, 0.25 pps Flocele, 5 pps Gilsonite (127 cu.ft.). Displace w/143.9 bbl wtr. Circ 90 bbl cmt to surface. WOC. PT BOP & csg To 1500 psi/30 min, OK. Drilling ahead.

3-4-01 Drill to TD @ 7791'. Circ hole clean.

3-5-01 TOOH. TIH w/182 jts 4 1/2" 10.5# J-55 ST&C csg, set @ 7790'. Pump 12 bbl mud flush ahead. Cmdt w/761 sx class "B" 50/50 poz w/3% gel, 0.9% fluid loss, 5 pps Gilsonite, 0.25 pps Flocele (1187 cu.ft.). Displace w/123.8 bbl wtr. Circ 25 bbl cmt to surface. WOC. PT csg to 3800 psi/15 min, OK. ND BOP. NU WH. RD. Rig released.



SIGNATURE

[Signature]

Regulatory Supervisor

March 7, 2001

no

(This space for State Use)

ORIGINAL SIGNED BY CHARLIE T. PETERSON

Title

Date

MAR - 8 2001

Approved by

X