Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

COPY

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. LEASE DESIGNATION AND SERIAL NO SF 079298B 078500 A SUNDRY NOTICES AND REPORTS ON WELLS 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals, reserving 7. IF UNIT OR CA, AGREEMENT DESIGNATION SUBMIT IN TRIPLICATE San Juan 28-7 Unit TYPE OF WELL 8. WELL NAME AND NO. OIL WELL GAS WELL OTHER San Juan 28-7 Unit #68 (NP) NAME OF OPERATOR 9. API WELL NO. CONOCO INC. 30-039-60071 ADDRESS AND TELEPHONE NO. 10. FIELD AND POOL, OR EXPLORATORY AREA 10 Desta Drive, Suite. 100W Midland, Texas 79705-450t Blanco Mesa Verde LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description) 11. COUNTY OR PARISH, STATE 990' FNL & 1650' FEL, UNIT LETTER "B", Sec. 31, T28N-R ONW Rio Arriba County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Final Abandonment Notice Casing Repair Water Shut-Off **Altering Casing** Conversion to Injection Other: CMT Squeeze Dispose Water (Note: Report results of multiple comp Recompletion Report and Log Form.) Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) RIH with 2 3/8" tubing with Hallib 4 1/2" cement retainer. Set retainer @ 4610', stung out of retainer and dropped down to tag retainer. Retainer had dropped to 4718'. Consulted with BLM, RIH with Hallib 4 1/2" cement retainer and set @ 4580'. Stung out and loaded casing. Rig up BJ to cement, stung into retainer and pumped 50 sks class B cement below retainer @ 4580'. Stung out of retainer and dumped 100' of cement on top of retainer, 11 sks on to of retainer. Pull tubing up to 4300', pumped 300' cement plug, 35 sks TOC @ 4000'. Pulled up the hole to 2887' and pumped 33 sks class B cement with 2% CCL. Approx TOC @ 2608'. Rig down BJ. POOH with 2 3/8" tubing. NOTE: MV is P&A permanent. Charca has cement plug 300' in casing. All cement work approved by Wayne Townsend BLM 5/27/99. RIH with 2 3/8" tubing with 6 1/8" bit. Tagged cement @ 2533'. Drilled cement to 2600'. Tested Csg to 300 psi -OK. POOH with 2 3/8" tubing with 6 1/8" bit. Rig up Blue Jet, run Gamma Ray strip log from 2600' to 2000'. Used log to correlate with open hole log. Perf Picture Cliff from 2564 - 68 , 2560 - 62 , 2538 - 40 , 2528 - 34 , 2518 - 23 , 2502 - 13 , 2493 - 97. All intervals shot with 3 1/8" HSC with 4 SPF. Total holes 136. RIH with 2 7/8" N - 80 tubing with Hallib 7 5/8" packer. 14. I hereby certify that the foregoing is true and correct TITLE VERLA JOHNSON, As Agent for Conoco Inc. AGGEP TERRIFOR DECOL (This space for Federal or State office use) AUG 0 5 1999 APPROVED BY TITLE Conditions of approval, if any: Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the Unites States arry false,

L.

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.