

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

2110' FNL, 2310' FEL

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVE

OCT 3 1963

U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

|   |  |
|---|--|
| NOTICE OF INTENTION TO DRILL                  | SUBSEQUENT REPORT OF WATER SHUT-OFF        |
| NOTICE OF INTENTION TO CHANGE PLANS           | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF    | SUBSEQUENT REPORT OF ALTERING CASING       |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REDRILLING OR REPAIR  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE       | SUBSEQUENT REPORT OF ABANDONMENT           |
| NOTICE OF INTENTION TO PULL OR ALTER CASING   | SUPPLEMENTARY WELL HISTORY                 |
| NOTICE OF INTENTION TO ABANDON WELL           |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 1, 19 63


Jicarilla Tribal 8-15

Well No. 1 is located 2110 ft. from ~~N~~ line and 2310 ft. from ~~E~~ line of sec. 15

SW  $\frac{1}{4}$  of NE  $\frac{1}{4}$ , Section 15 28N 1W NMPM  
( $\frac{1}{4}$  Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Boulder-Mancos Rio Arriba New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7394 ft.



DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 9-10-63, Moved in equipment, rigged up unit. Dug out cellar and broke out wellhead connections.
- 9-11-63, Rigged up casing jacks. Spotted 15 sx. cement plug 4375 to 4150', down 5  $\frac{1}{2}$ " casing.
- 9-12-63, Worked casing free to 2000'. Shot 5  $\frac{1}{2}$ " casing at 2750', attempted to pull. Shot 5  $\frac{1}{2}$ " casing free at 2505'. Spotted 25 sx cement plug across stub from 2550-2450'. Laid down 1150' 5  $\frac{1}{2}$ " casing.
- 9-13-63, Spotted 25 sx. cement plug at 1350' thru 5  $\frac{1}{2}$ " casing. Laid down 1350' of casing. Installed dry hole marker with 10 sx cement surface plug. Rig down, move off location.
- 9-26-63, Location leveled and cleared. Well officially plugged and abandoned, September 26, 1963.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, A Division of California Oil Company

Address Drawer "S"

Monahans, Texas

By *G. G. Koenig* G. G. Koenig

Title Lead Engineer