

ILLEGIBLE

Budget Bureau No. 42-R359.4.
Approval expires 12-31-60.

Form 9-331 b
(April 1952)

(SUBMIT IN TRIPLICATE)


Indian Agency _____

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Flourilla Apache

Allottee _____

Lease No. 20



990' E & 1980' N

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	<input type="checkbox"/>	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	<input type="checkbox"/>	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	<input type="checkbox"/>	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	<input type="checkbox"/>	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input type="checkbox"/>	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	<input type="checkbox"/>		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 11, 1962

Flourilla 4-26

Well No. 6 is located 990 ft. from N line and 1980 ft. from E line of sec. 36

1/4 of 36, Sec. 36

20N

1W

104N

(1/4 Sec. and Sec. No.)

(Twp.)

(Range)

(Meridian)

Boulder-House

Big Arriba

New Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the derrick floor above sea level is 7262 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

Notice is hereby given of intention to drill the Flourilla 4-26 36 to a total depth of approximately 4730 feet with rotary tools. 12" surface hole will be drilled to 100 feet where 100 feet of 3-5/8", 36#/ft., J-55, HMC new casing will be landed & cemented with cement to surface. 8-1/4" hole will be drilled below surface casing with mud to approximately 4330 feet. 7", 36#/ft., J-55, HMC new casing will be landed & cemented at approximately 4330 feet with 200 cc cement. Drilling will continue in 6" hole to total depth substituting air for drilling fluid. Logs will be run. 5/8", 15.2#/ft., J-55, Plug-joint slotted liner will be set at total depth if commercial production is obtained. Primary objective is the Gallup formation.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Standard Oil Company of Texas, a Division of California Oil Company

Company _____

Derrick "B"

Address _____

Mountain, Texas

By J. L. Howard

District Engineer

Title _____