

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☐  
well well

2. NAME OF OPERATOR

Petroleum Energy

3. ADDRESS OF OPERATOR

Box 2121 Durango, Co 81301

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: SW SW : 660' fr S & 660' fr W

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

RECEIVED

FEB 15 (NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT  
HARMINGTON RESOURCE AREA

5. LEASE

N00-C-14-5420

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Navajo

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Staver-Navajo

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Unnamed (North Tocito)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SW SW Sec. 34, T27N-18W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5624' GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Received verbal approval to abandon. See attached sheet.

RECEIVED  
DEC 19 1985  
OIL CON. DIV. 1  
DIST. 3  
Set 3

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY:

Approved as to plugging of the well bore.  
Liability under bond is retained until  
surface restoration is completed.

PR OK 3-22-1985

See Instructions on Reverse Side  
FARMINGTON COPY  
NMOC

FEB 22 1985  
M. MILLENBACH  
AREA MANAGER

APPROVED  
AS AMENDED

RECOMPLETION ATTEMPT BY PETROLEUM ENERGY, INC., ON THE # 1  
STAVES - SINCLAIR LOCATED IN THE SW $\frac{1}{4}$ SW $\frac{1}{4}$  OF SECTION 34, TOWNSHIP  
27 NORTH, RANGE 18 WEST, SAN JUAN COUNTY, NEW MEXICO.

- 11-19-84 SQUEEZED WITH 200 SX CEMENT THE EXISTING PERFS (6717'-6720',  
TO 6730'-6740', 6742'-6744', 6752'-6758', 6763'-6774', 6778'-6786',  
11-30-84: 6794'-6802'). RE-PERFED 6717'-6720', 6730'-6740', 6746'-6749',  
6797'-6762' WITH 2 PER FOOT
- 12-01-84: ACIDIZED WITH 4000 GALLONS OF 28% HCL. PRESSURED UP TO 4000#,  
BROKE BACK TO 2000#. SWABBED SALT WATER AT 80 BBLs PER HOUR;  
NO GAS.
- 12-02-84: SET BP AT 6743'-6744' - TREATED WITH ATOMIZED ACID 15% HCL  
THE PERFS 6717'-6720' & 6730'-6740, 300 GALLONS & 50,000 SCF N<sub>2</sub>.
- 12-03-84: PRESSURE WELLHEAD 660#; FLUID LEVEL 900 FEET, SWABBED 8 BBLs PER  
HOUR & 90 MCFG/D - NOT COMMERCIAL.
- 12-04-84: PLACED 100 FOOT CEMENT PLUG 6743' TO 6643'; WAITING ON CEMENT.
- 12-05-84 SHOT 3 HOLE AT 4500' AS MUD WEEP HOLE BETWEEN 7" & 9 5/8" STRINGS  
TO HAD MUD AND WATER FLOW (HOT) AT 80 BBLs PER HOUR, FRESH. SQUEEZED  
12-06-84: WITH 125 SX CEMENT. CEMENT TOP 3942' BY TEMPERATURE SURVEY.
- 12-07-84: SHOT 3 HOLES (DML-23) AT 4420' AS TEST HOLES FOR CEMENT SQUEEZED  
JOB OF YESTERDAY. NO WATER MOVEMENT, FLUID LEVELS STILL AT 200  
FEET. WELL IN ESSENCE DEAD. PERF ORGAN ROCK, 3 RUNS, 1 SHOT PER  
FOOT; 4425'-4445', 4445'-65 & 4465' TO 4485' (DML-23). WATER  
FLOW TO SURFACE AFTER LAST RUN. FLOW RATE APPROXIMATELY 3 BBLs  
PER HOUR FRESH (COLD) WATER. (NO GAS). BELIEVED FLOW WAS  
CHANNELED OUTSIDE 9 5/8" CASING. IT HAD DRILLING MUD IN IT.  
DECISION MADE TO QUIT THE HOLE. SET BRIDGE PLUG AT 4375' AND  
PLUGGED ACCORDING TO BLM AS FOLLOWS: 100' CEMENT PLUG, 25 SX,  
4375'-4275'. 42 SX 9.2# AQUAGEL MUD 4275'- 450', 100' CEMENT  
PLUG 450' TO 350', MUD 350' TO 50', CEMENT PLUG 50' TO 10'. DONE  
AT 11:00 PM. WILL ERECT IRON MONUMENT WITH WELL DATA SET IN 10'  
CEMENT.