

MAY 30 1956  
RECEIVED  
(Orig. Sgd.) P. T. McGrath  
DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Santa Fe  
Lease No. 077973  
Unit E. H. Newman

## SUNDRY NOTICES AND REPORTS ON WELLS

|  |                                     |  |  |
|--|-------------------------------------|--|--|
| NOTICE OF INTENTION TO DRILL                   |                                     | SUBSEQUENT REPORT OF WATER SHUT-OFF        |  |
| NOTICE OF INTENTION TO CHANGE PLANS            |                                     | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |  |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     |                                     | SUBSEQUENT REPORT OF ALTERING CASING       |  |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL |                                     | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |  |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        |                                     | SUBSEQUENT REPORT OF ABANDONMENT           |  |
| NOTICE OF INTENTION TO PULL OR ALTER CASING    |                                     | SUPPLEMENTARY WELL HISTORY                 |  |
| NOTICE OF INTENTION TO ABANDON WELL            | <input checked="" type="checkbox"/> |  |  |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico May 30, 1956Well No. 1 is located 660 ft. from NU line and 660 ft. from E line of sec. 31SE/4 of Section 31 T-27-N R-13-W NMPM  
( $\frac{1}{4}$  Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wildcat San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 6185 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to plug the above well in the following manner:

- 1) Set 60 sack cement plug from 5900 to 5738 feet.
- 2) Set 60 sack cement plug from 4150 to 3988 feet.
- 3) Set 60 sack cement plug from 2150 to 1988 feet.
- 4) Set 70 sack cement plug from 1400 to 1215 feet.
- 5) Set 50 sack cement plug at bottom of surface pipe, 525 feet.
- 6) Set 10 sack cement plug at surface and erect 4-foot pipe marker.
- 7) Hole filled with mud between plugs.
- 8) Restore ground to original contour.

Verbal approval received 5/30/56, P. T. McGrath to L. O. Speer,

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company STANDARD OIL & GAS COMPANYAddress FARMINGTON, NEW MEXICOBy L. O. SpeerTitle Field Superintendent