FOR (F	eb. 19	531 H (51)	

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

App	O Tal Cap	
Land Office	ña <b>v</b>	Mexico
Lease No	010	
Unit	bie	rfano

## CLINDDY NOTICES AND REPORTS ON WELLS

SUNDRY NOTICES	
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZATE
OTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF ALTERNITO
OTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO PULL OR ALTER CASING	Water Fracture
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHEC	CK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	December 3, 19 <sup>50</sup>
Vell No. 34 is located 390 ft	t. from $\{S\}$ line and $\frac{991}{S}$ ft. from $\{E\}$ line of sec. $\frac{36}{S}$
(½ Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
and the state of t	S.a. Juan
(Field)	(County or Subdivision) (State or Territory)
itate names of and expected depths to objective sands ing points	DETAILS OF WORK  1; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen 1; and all other important proposed work)
State names of and expected depths to objective sands ing points.  12-2-50 C.O.T.D. 2121.	DETAILS OF WORK  1; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen 1; and all other important proposed work)
State names of and expected depths to objective sands ing points.  12-2-50 C.C.T.D. 2121.  Water fractured fictured Cliff water and 25,000; sand. Break everage treating pressure 1800 gallons. Natural gage name.  I understand that this plan of work must receive a Company El laso Natural Gage	DETAILS OF WORK  s; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen s; and all other important proposed work)  perforated intervals 2050-64 with 29,232 gallow idown pressure 1500%, miximum pressure 1800%,  Injection rate 64.5 BM. Flush 2100  ACCOMPANY  Approal in writing by a Geological Survey before operations may be commenced.
State names of and expected depths to objective sands ing points.  12-2-50 C.O.T.D. 2121.  Water fractured Fictured Cliff water and 25,000; sand. Break average treating pressure 1800 gallons. Natural gage none.	DETAILS OF WORK  Is, show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen is, and all other important proposed work)  Perforated intervals 2050-64 with 29,232 gallow idown pressure 1500%, maximum pressure 1600%, injection rate 64.5 BM. Flush 2100  PERFORMANCE OF THE CONTROL OF THE PROPOSED OF THE CONTROL

-