

6 BLM 1 File 1 Ft. Collins Cons. Roy.
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 1650' FWL
Sec. 34, T27N, R10W, NMPM

5. Lease Designation and Serial No.

SF 081087

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

McAdams #4

9. API Well No.

10. Field and Pool, or Exploratory Area

Basin Dakota-Angel Pk.GA.

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to the work.)

Plug well as follows:

1. Spot 300' plug from 4750' inside 7-5/8" casing.
2. Perforate below Pictured Cliffs @ 2500'.
3. Set cement retainer @ 1950'.
4. Pump 200 cu. ft. Class B cement below retainer to cover Pictured Cliffs and Fruitland tops.
5. Perforate below Ojo Alamo @ 1528'.
6. Pump 150 cu. ft. Class B cement to cover to Ojo Alamo top @ 1360' inside and outside casing.
7. Perforate 50' below surface casing set @ 192' and pump cement to fill inside and outside 7-5/8" to the surface.
8. Set dry hole marker.

Spot 8.34 lb./gal., 40 sec./qt. mud between plugs. This weight mud will control any formation pressures encountered in this well bore.

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct

Signed John Alexander
(This space for Federal or State office use)

Title Operations Manager

Date 12/16/92

Approved by _____
Conditions of approval, if any:

Title

NMOCD

Date DEC 18 1992

AREA MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.