

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

NMSF-079232

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Bolack C LS

6

9. API Well No.

3004506121

10. Field and Pool, or Exploratory Area

Ballard Pictured Cliffs Gas

11. County or Parish, State

San Juan

New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

Pat Archuleta

3. Address and Telephone No.

P.O. BOX 800 DENVER, COLORADO 80201

303-830-5217

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650'FSL

1560'FEL

Sec. 31 T 27N R 8W

UNIT J

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRUSU 2/10/97

Set CIBP at 1934'. tested csg to 500#. Held okay.

Set cmt plug inside csg from 1934'-1651', w/32 sks CI-B cement.

Perf at 1328', set cmt ret at 1251', squeeze perms at 1328' w/167 sks CI-B cement from 1328'-980', inside and outside 5.5" csg.

Shoot squeeze holes at 185'. Spot cmt plug at 1139' inside csg to perms at 185', w/129 sks CI-B cement, had circ but lost circ after pumping 8bbbls squeeze cmt outside 5.5" csg.

Pump 50sks CI-B cement dn 5.5" annulus.

Tag cmt inside 5.5" csg at 80', cut off wellhead and fill 5.5" and 9.5" csg to surface w/21 sks CI-B cement. Install marker

RDMOSU 2/12/97

14. I hereby certify that the foregoing is true and correct

Signed

Pat Archuleta

Title

Staff Assistant

Date

02-24-1997

(This space for Federal or State office use)

Approved by

AS/ Duane W. Spencer

Title

Date

MAR 6 1997

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

* See Instructions on Reverse Side