For (I	m 9- Feb. 19	9 331 a 951)	
		_	
		·	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	· · · · · · · · · · · · · · · · · · ·
Lease NNM	03413
Unit	
Morean	Endaral

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS.	
NOTICE OF INTENTION TO TEST WATER SHU	
NOTICE OF INTENTION TO RE-DRILL OR RE	PAIR WELL SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDI	IZESUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER	CASINGSUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL.	
(INDICATE ABO	OVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	June 9, 16
Well No. 1 is located 8	50 ft. from ${\mathbb{K} \choose S}$ line and 1850 ft. from ${\mathbb{K} \choose W}$ line of sec. 36
1/4 SE/4 Sec. 36	27N 12N NMPM (Twp.) (Range) (Meridian)
,	San Juan New Hextan
(Field)	(County or Subdivision)
The elevation of the desired	or above sea level i6014 ft.GL / KLLSLIV LL
the elevation of the constant	
	DETAILS OF WORK DEC 1 4 1960
State names of and expected depths to object	ctive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cerr
	ctive sands; show sizes, weights, and lengths of proposed casings; indicate mudifications, cerring points, and all other important proposed work)
State names of and expected depths to object	ctive sands; show sizes, weights, and lengths of proposed casings; indicate mudible lebs, cerr ing points, and all other important proposed work)
oudded 2-16-60 -17-60 ran and set 29	ctive sands; show sizes, weights, and lengths of proposed casings; indicate middle less, con ing points, and all other important proposed work) 5' of 10 3/4" 32.75# casing at 308' KB Meas regular 25 CC, plug down 10 A. M. 4 hrs w/600# pressure, held CK.
oudded 2-16-60 -17-60 ran and set 29 emented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o	of 10 3/4" 32.75# casing at 308' KB Meas regular 2% CC, plug down 10 A. M. MA hrs w/600# pressure, held CK. of 11.60# 4%" csg. set at 6259' KB cemented
oudded 2-16-60 -17-60 ran and set 29 emented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o	of 10 3/4" 32.75# casing at 308' KB Meas regular 2% CC, plug down 10 A. M. MA hrs w/600# pressure, held CK. of 11.60# 4%" csg. set at 6259' KB cemented
oudded 2-16-60 -17-60 ran and set 29 emented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o	of 10 3/4" 32.75# casing at 308' KB Meas regular 2% CC, plug down 10 A. M. MA hrs w/600# pressure, held CK. of 11.60# 4%" csg. set at 6259' KB cemented
oudded 2-16-60 -17-60 ran and set 29 emented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o	of 10 3/4" 32.75# casing at 308' KB Meas regular 2% CC, plug down 10 A. M. MA hrs w/600# pressure, held CK. of 11.60# 4%" csg. set at 6259' KB cemented
oudded 2-16-60 -17-60 ran and set 29 emented with 250 sx r -18-60 tested after 2	of 10 3/4" 32.75# casing at 308' KB Meas regular 2% CC, plug down 10 A. M. MA hrs w/600# pressure, held CK. of 11.60# 4%" csg. set at 6259' KB cemented
oudded 2-16-60 -17-60 ran and set 29 mented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o with 400 sx: 200 sx 4	of 10 3/4" 32.75# casing at 308' KB Meas regular 2% CC, plug down 10 A. M. M. A hrs w/600# pressure, held CK. of 11.60# 4%" csg. set at 6259' KB cemented & Gel / 200 2% Gel. Tested en 5-8-60 held C
oudded 2-16-60 -17-60 ran and set 29 mented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o with 400 sx: 200 sx 4	of 10 3/4" 32.75# casing at 308' KB Meas regular 2% CC, plug down 10 A. M. MA hrs w/600# pressure, held CK. of 11.60# 4%" csg. set at 6259' KB cemented
oudded 2-16-60 -17-60 ran and set 29 emented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o with 400 sx: 200 sx 4	of 10 3/4" 32.75% casing at 308' KB Meas regular 2% CC, plug down 10 A. M. M. M. hrs w/600% pressure, held CK. of 11.60% 4%" csg. set at 6259' KB comented & Gel / 200 2% Gel. Tested on 5-8-60 held Comented on 5-8-60 held C
oudded 2-16-60 -17-60 ran and set 29 mented with 250 sx r -18-60 tested after 2 3-7-60 Ran 199 jts. o with 400 sx: 200 sx 4	of 10 3/4" 32.75% casing at 308' KB Meas regular 2% CC, plug down 10 A. M. M. A hrs w/600% pressure, held CK. of 11.60% 4%" cag. set at 6259' KB comented as Gel / 200 2% Gel. Tested on 5-8-60 held Company. Conter Bldg
oudded 2-16-60 17-60 ran and set 29 mented with 250 sx r 18-60 tested after 2 1-7-60 Ran 199 jts. o with 400 sx: 200 sx 4	of 10 3/4" 32.75% casing at 308' KB Meas regular 25 CC, plug down 10 A. M. M. hrs w/600% pressure, held CK. of 11.60% 4%" csg. set at 5259' KB comented in Gel / 200 2% Gel. Tested on 5-8-60 held Company. Center Bldg. Original signed by
oudded 2-16-60 17-60 ran and set 29 mented with 250 sx r 18-60 tested after 2 1-7-60 Ran 199 jts. o with 400 sx: 200 sx 4	of 10 3/4" 32.75% casing at 308' KB Meas regular 2% CC, plug down 10 A. M. M. A hrs w/600% pressure, held CK. of 11.60% 4%" csg. set at 6259' KB comented as Gel / 200 2% Gel. Tested on 5-8-60 held Company center Bldg. Original signed by Carl W. Smith