

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 12030

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Nassau

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Undesignated - PC

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 36, T27N, R12W

12. COUNTY OR PARISH

San Juan

13. STATE

NM

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

Jerome P. McHugh

3. ADDRESS OF OPERATOR

Box 234, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface

1850' FSL - 1450' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6012' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-14-76

Spudded 7-14-76. Drilled 8-3/4" hole to 75' and ran 2 jts 7" OD "B" condition csg. TE 72.76' set @ 77' RKB. Cemented by BJ w/35 sx Class "B" neat with 2% CaCl. POB @ 7:00 PM 7-14-76.

7-20-76

TD 1600'. Ran 50 jts 2-7/8" OD 6.5# J-55 8R EUE "new" tbg for csg. TE 1577.80' set @ 1582' RKB. Cemented w/90 sx BJ 2% Lodense with 1/4# Cello-flake/sk. Re- reciprocated pipe and had good circulation during cementing operations. Bumped plug w/1800 psi, released to 800 psi, and shut well in. POB 12:00 noon 7-20-76.

RECEIVED

AUG 13 1976

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

18. I hereby certify that the foregoing is true and correct

SIGNED

Thomas A. Dugan
Thomas A. Dugan

TITLE

Engineer

DATE

8-12-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: