

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.
SF-078089

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Scott E. Fed #6

9. API Well No.

3004506162

10. Field and Pool, or Exploratory Area

West Kutz PC

11. County or Parish, State

San Juan, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Bonneville Fuels Corporation

3. Address and Telephone No.

1660 Lincoln, Suite 1800, Denver, CO 80264 (303) 863-1555

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FNL, 990' FWL Sec 36 T27N R11W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Bonneville Fuels Corporation proposes to P&A the subject well as follows:

- 1.) Set cement retainer @ +/- 2025' and squeeze the Pictured Cliffs formation w/ 300 sx Class B Cement.
- 2.) Pull out of retainer and spot a 150' cement plug plus 50% excess from 2025' to 1875'.
- 3.) Spot a cement plug from 1175' to 970' (100% excess).
- 4.) Perforate at 170' and circulate cement to the surface, leaving the 5 1/2" casing full of cement.

Note: 9.0 lbs/gal mud is to be placed between all plugs.

14. I hereby certify that the foregoing is true and correct

Signed

Title Engineering Technician

Date 7/27/92

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

APPROVED

JUL 30 1992

AREA MANAGER

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD