


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 37922
Unit Dolinet



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 30-6 is located 70 ft. from N line and 22 ft. from E line of sec. 33
33 Sec. 33 27N ON N.H.P.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco H.V. Dist. 2 San Juan New Mexico
 (Field) (County or Subdivision) (State or Territory)

South Blanco P.C. Dist.
The elevation of the derrick floor above sea level is 2751 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

June 2, 1950--Set magnesium drillable bridge plug 22547'.
 Set retrievable cementer 22568'.
 Spaced Pictured Cliffs perforated intervals 2750-2760; 2760-2770;
 2770-2800; 2810-2820 with 100 sacks neat cement and 25 CaCl.
 Put approximately 70 sacks cement through perforations.
 Maximum and final pressure 3000 psi.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997
Harrison, New Mexico

By Original Signed D. C. Johnston

Title Petroleum Engineer

