



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 49232
Unit Block

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	WATER PUMP

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 24, 1954

Well No. 16-0 is located 110 ft. from [N] line and 110 ft. from [E] line of sec. 35
24 1/4 Sec. 35 24 N 04 W N.S.P.M.
Twp. Range Meridian
Co. Blanco P. M. San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6152 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 0-10-01 T.D. 5223'. C.O.T.D. 5235'. Water fractured Point Lookout perf. int. 4770-48; 4940-50; 5056-5000; 5022-44; 5056-66; 5076-66; 5094-5110; 5120-40; 5140-66 w/2 10/ft. w/70,000 gallons water and 70,000% sand. Max. pr. 3000%, avg. tr. pr. 2400%. I.R. 50 BHM. Flush 6400 gallons. Natural gas TSM MCF/D.
- 0-10-02 T. D. 5243'. Temporary bridge plug at 4760'. Water fraced fractured CLAYs perf. int. 2764-66; 2790-2800; 2810-24 w/2 10/ft. w/40,000 gallons water and 40,000% sand. HD pr. 2500%, max. pr. 3000%, avg. tr. pr. 2300%. I.R. 50 BHM. Flush 5700 gallons. Natural gas TSM MCF/D.
- 0-17-01 T. D. 5205'. Water fractured Point Lookout perf. int. 4070-66; 4940-50; 4940-5000; 5022-44; 5056-66; 5076-66; 5094-5110; 5120-40; 5140-66 w/2 10/ft. w/67,200 gallons water & 75,000% sand. Max. pr. 3200%, avg. tr. pr. 2400%. I.R. 53 BHM. Flush 6400 gallons. Natural gas TSM MCF/D.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

LA Paso Natural Gas Company

Company LA Paso Natural Gas Company

Address Box 271

Flamingo, New Mexico

By Original Signed D. C. Johnston

petroleum Engineer

Title