

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 11, 1955

(Date)

Farmington, New Mexico.

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

J. Glenn Turner (Company or Operator) Huerfano Unit (Lease)
Huerfano Drilling Co., Inc. (Contractor), Well No. 10-36 in the NE 1/4 NE 1/4 of Sec. 36

T. 27 N., R. 9 W., NMPM, Wildcat Pool, San Juan County.

The Dates of this work were as follows: May 26 - June 10, 1955.

Notice of intention to do the work (was) ~~not~~ submitted on Form ~~C-101~~ ^{C-102} on May 13, 1955, 19
(Cross out incorrect words)

and approval of the proposed plan (was) ~~not~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

May 28, 1955. After drilling to 2020' with rotary rig, found top of Pictured Cliffs at 2,215'. Ran 61 joints (2012') of 5-1/2" 14# casing to 2020' R.K.P. Cemented with 100 sacks cement. Moved rotary off.

June 5, 1955. Moved in cable tools. Three hour water test showed hole dry. On 6/6/55 loaded with 130 quarts solidified nitro glycerin from 2030 - 2086'. Tamped with 110' of gravel. On 6/8/55 unloaded hole. After 12 hours flowed 215 MCF/day.

June 9, 1955. Sand oil treated ~~at~~ from 2020' to 2086' with 8,000 gallons diesel oil, and 11,400# sand. Flushed with 2,200 gallons diesel. Breakdown 1050#; Maximum 1050#; Minimum 900#. Injection ~~at~~ 33.2 B.P.M. Unloaded hole.

June 10, 1955. After 24 hours - flowing 760 MCF/day. Ran 97 joints of 1" tubing to 2015'. Shut well in for potential test.

Witnessed by Oliver L. Lowell & C. F. Stringer - Huerfano Drilling Co., Inc. Tool Pushers
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION Arnold
Original Signed Entry

(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name G. Beurot Neal

Position G. Beurot Neal, Agent in Farmington

Representing J. Glenn Turner

Address Box 728 - Farmington, New Mexico.

Oil and Gas Inspector Dist. #3.

(Title)

JUN 15 1955

(Date)

OIL FIELD INVESTIGATION COMMISSION

AT THE FIELD OFFICE

No. Co.

Operator

Santa Fe

Production

State

U. S. G. S.

Transporter

File