⊱R358.4. l–60.
6
-

Land Office	
Lease No.	SF-078896
Unit	
Mudge	Federal

GPO 862040

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL SUBSCULUTI REPORT OF SHOOTING OR ACIDIZING. NOTICE OF INTENTION TO TEST WATER SHUT-OFF SUBSCULUTI REPORT OF SHOOTING OR ACIDIZING. NOTICE OF INTENTION TO TEST WATER SHUT-OFF SUBSCULUTI REPORT OF ALTERING CASING. NOTICE OF INTENTION TO REDRILL OR REPAIR WELL.  NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO DULL OR ALTER CASING. NOTICE OF INTENTION TO DULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)	NOTICE OF INT	ENTION TO DRILL		X sui	SEQUENT REPORT	OF WATER SHUT-OF	F
Subsequent report of alterno casing subsequent report of alterno casing subsequent report of recording or report of report							
Subsequent Report of Re-DellLing or Repair well.  Subsequent Report of Re-DellLing or Repair well.  Subsequent Report of Re-DellLing or Repair well.  Subsequent Report of Reduction of Adambon well.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  May 12 , 19 61  May 12 , 19 61  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE BY CHECK MARK NATURE OF REPORT OF ABANDONMENT.  (INDICATE BADDON MARK NATURE OF REPORT OF ABA							
Subsequent report of Abandonment.  Subsequent report, Notice, or other Data)  May 12 , 9 61  May 13 , 9 6  May 14 , 9 6  May 14 , 9 6  M							
(NDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  May 12 , 19 61  May 12				ľ			
(MDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)  May 12 , 19 61  May 12				SUI	PLEMENTARY WELI	L HISTORY	
(NDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)    May 12							
/ell No. 4 is located 790 ft. from Nap line and 1030 ft. from Nap line of sec. 33 27N 11W Nap Mark Sec. 34 27N 11W Nap Mark Sec. 35	NOTICE OF INT	ENTION TO ABANDON W	L				
Well No. 4 is located 790 ft. from the line and 1030 ft. from the line and		(INDICATE	ABOVE BY CHECK MAR	K NATURE	OF REPORT, NOTICE	, OR OTHER DATA)	
(k) Sec. 33  27N  11W  (k) Sec. and Sec. No.)  (Twp.)  (Range)  (Range)  (Meridian)  (State or Territory)  MAY 16  15  DETAILS OF WORK  Internation of the derrick floor above sea level is 6218.7ft. G.1.  DETAILS OF WORK  Internation of and expected depths to objective sands; show since, weights, and lengths of proposed casings; indicate mudding sighs, camenting points, and all other important proposed work)  Tropose to drill with rotary tools to an approximate depth of 6600° or to test the Dakota formation. Casing program will be as follows:  0 3/4" 32.30# surface set at approximately 200° with 160 sx cement.  10.50# set at total depth with 475 sx cement, or cement to cover sallup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  Funderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company  Southwest Production Company  Address  162 Petr. Center Bldg.,  Original signed by Carl W. Smith  Farmington, New Mexico				*		<u></u>	ay 12 , 19.6
(K) Sec. and Sec. No.)  (Twp.)  (Range)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy)  (Alty 16 15  (State or Tertiopy)  (State or Tertiopy) (	'ell No	4 is locate	d 790 ft. from	$n = \begin{bmatrix} N \\ M \end{bmatrix}$	ine and <b>10</b>	$30$ ft. from $\binom{13}{W}$	line of sec. 33
(X Sec. and Sec. No.)  San Juan  (County or Subdivision)  (State or Territory)  MAY 1 6 15  DETAILS OF WORK  DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work)  repose to drill with rotary tools to an approximate depth of 6600° or to test the Dekota formation. Casing program will be as follows:  0 3/4" 32.50# surface set at approximately 200° with 160 sx coment.  10 50# set at total depth with 475 sx coment, or coment to cover allup formation.  (I) tool will be set for the protection of the Pictured Cliffs formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company  Southwest Production Company  Address  162 Petr. Center Bidg.,  Criginal signed by Carl W. Smith  By					NO.	(eridian)	RFIF
country or Subdivision)  (State or Territory)  MAY 16 19  DETAILS OF WORK  Internames of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work)  repose to drill with rotary tools to an approximate depth of 6600° or to test the Dakota formation. Casing program will be as follows:  0.3/4" 32.50# surface set at approximately 200° with 160 sx coment.  10.50# set at total depth with 475 sx coment, or coment to cover allup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bidg.,  Parmington, New Mexico By  Carl W. Smith  By			,		(24		Mexico 'Malj!
DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work)  repose to drill with rotary tools to an approximate depth of 6600' or to test the Dakota formation. Casing program will be as follows:  0.3/4" 32.50# surface set at approximately 200' with 160 sx coment.  2" 10.50# set at total depth with 475 sx coment, or coment to cover allup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bidg.,  Parmington, New Mexico By	sin Dake	ota	County	or Subdivi	sion)		
DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding igbs, cementing points, and all other important proposed work)  repose to drill with retary tools to an approximate depth of 6600° or to test he Dakota formation. Casing program will be as follows:  0.3/4" 32.50# surface set at approximately 200° with 160 sx cement.  10.50# set at total depth with 475 sx cement, or cement to cover allup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  111 perforate and sand-water frac the Dakota formation.  1 understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bldg., Original signed by Carl W. Smith  By	,	•					16
DETAILS OF WORK  tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding igbs, cementing points, and all other important proposed work)  ropose to drill with rotary tools to an approximate depth of 6600° or to test he Dakota formation. Casing program will be as follows:  0.3/4" 32.50# surface set at approximately 200° with 160 sx cement.  10.50# set at total depth with 475 sx cement, or cement to cover allup formation.  11 perforate and sand-water frac the Dakota formation.  12 understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  13 Company Southwest Production Company  Address 162 Petr. Center Bldg.,  162 Petr. Center Bldg.,  163 Petr. Center Bldg.,  164 Petr. Center Bldg.,  165 Petr. Center Bldg.,  166 Petr. Center Bldg.,  167 Petr. Center Bldg.,  168 Petr. Center Bldg.,  169 Petr. Center Bldg.,  169 Petr. Center Bldg.,  169 Petr. Center Bldg.,  160 Petr. Center Bldg.,  161 Petr. Center Bldg.,  162 Petr. Center Bldg.,  163 Petr. Center Bldg.,  164 Petr. Center Bldg.,  165 Petr. Center Bldg.,  166 Petr. Center Bldg.,  167 Petr. Center Bldg.,  168 Petr. Center Bldg.,  169 Petr. Center Bldg.,  160 Petr. Center Bldg.,  160 Petr. Center Bldg.,  160 Petr. Center Bldg.,  160 Petr. Center Bldg.,  161 Petr. Center Bldg.,  162 Petr. Center Bldg.,  164 Petr. Center Bldg.,  165 Petr. Center Bldg.,  167 Petr. Center	ha alawatia	on of the derrick	floor above sea le	evel is 1	218.7 ft. G.	L.	1016
repose to drill with retary tools to an approximate depth of 6600° or to test he Dakota formation. Casing program will be as follows:  0 3/4" 32.50# surface set at approximately 200° with 160 sx coment.  10.50# set at total depth with 475 sx coment, or coment to cover sallup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bldg., Original signed by Carl W. Smith  By Harmington, New Mexico	He elevatio	of the derries.					1960
repose to drill with rotary tools to an approximate depth of 6600° or to test he Dakota formation. Casing program will be as follows:  0 3/4" 32.50# surface set at approximately 200° with 160 sx coment.  2" 10.50# set at total depth with 475 sx coment, or coment to cover sallup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  Fill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bidg.,  Parmington, New Mexico By			DETA	ILS O	F WORK		
repose to drill with rotary tools to an approximate depth of 6600' or to test he Dakota formation. Casing program will be as follows:  0 3/4" 32.50# surface set at approximately 200' with 160 sx coment.  10.50# set at total depth with 475 sx coment, or coment to cover allup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  Hill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bldg.,  Parmington, New Mexico By		1 and denthe to	objective sands: show s	izes, weigh	ts, and lengths of	proposed casings; in	dicate mudding jobs, cemer
repose to drill with rotary tools to an approximate depth of 6600' or to test he Dakota formation. Casing program will be as follows:  0 3/4" 32.50# surface set at approximately 200' with 160 sx coment.  10.50# set at total depth with 475 sx coment, or coment to cover allup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  Hill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bldg.,  Parmington, New Mexico By	tate names of	and expected depths to	ing points, and all	other imp	ortant proposed w	ork)	
he Dakota formation. Casing program will be as lettower.  0 3/4" 32.50# surface set at approximately 200' with 160 sx cement.  10.50# set at total depth with 475 sx cement, or cement to cover sallup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  Hill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bidg., Original signed by Carl W. Smith  Farmington, New Mexico		a dud 1) with s	rotery tools	to an	epproximate	e depth of (	6600' or to test
0 3/4" 32.50# surface set at approximately 200' with 160 sx cement.  2" 10.50# set at total depth with 475 sx cement, or cement to cover sallup formation.  DV tool will be set for the protection of the Pictured Cliffs formation.  Fill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bidg., Original signed by Carl W. Smith  Farmington, New Mexico	he Dakoti	a formation.	Casing progr	em wil	l be as fol	llows:	
is 10.50% set at total depth with 475 sx commit, or constitute to consideration.  DV tool will be set for the protection of the Pictured Cliffs formation.  Hill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bldg., Original signed by Carl W. Smith  Farmington, New Mexico							_
is 10.50% set at total depth with 475 sx commit, or constitute to consideration.  DV tool will be set for the protection of the Pictured Cliffs formation.  Hill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company Southwest Production Company  Address 162 Petr. Center Bldg., Original signed by Carl W. Smith  Farmington, New Mexico	0 3/4" 3	2.50# surface	set at appro	ximate	ly 200' wi	th 160 ex c	esent.
In the set for the protection of the Pictured Cliffs formation.  Fill perforate and sand-water frac the Dakota formation.  I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company  Southwest Production Company  Address  162 Petr. Center Bldg.,  Carl W. Smith  By	10.50	# set at total	l depth with	475 sx	cement, o	r cement to	COVEZ
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.  Company  Southwest Production Company  Address  162 Petr. Center Bidg.,  Carl W. Smith  By	•		for the prote	ction	of the Pic	tured Cliff	s formation.
Company Southwest Production Company  Address 162 Petr. Center Bldg., Original signed by Carl W. Smith  Farmington, New Mexico By	fill perf	forate end san	d-water frac	the D	kota forma	tion.	
Address 162 Petr. Center Bldg., Original signed by Carl W. Smith  By	I understan	d that this plan of work	must receive approval	in writing	by the Geological	Survey before opera	ations may be commenced.
Address 162 Petr. Center Bldg., Original signed by Carl W. Smith  By	Company	Southwest P	roduction Com	pany			
Farmington, New Mexico							
Farmington, New Mexico		140 Baka C				الممالية إن الأثر	staned by
	Address	140 Baka C				Original	signed by
CL 6 Till Deaduction Superintendent	Address	162 Petr. C	enter Bldg.,		<b>D.</b> .	Carl W.	signed by Smith
	Address	162 Petr. C	enter Bldg.,		Ву	Carl W.	signed by Smith

N IBEN OF COPI	- ALCEIV		
011	TRIBUTIO	N	
BANTA FF			
FILE			
U.S.G.S.		,	
LAND OFFICE			
	OIL		
TRANSPORTER	@AS		
PROBATION OFFI	CE		
OPERATOR			

## NEW MEXICO OIL CONSERVATION COMMISSION

FORM C-128

FILE					Revised 5/1/5/		
LAND OFFICE		WELL LOCA	TION AND ACRE	EAGE DEDICAT	TION PLAT		
YRANSPORTER GAS		SEE INSTRUCTIO	NS FOR COMPLETING	THIS FORM ON THE	REVERSE SIDE		
PRORATION OFFICE OPERATOR							
Operator	· · · · · · · · · · · · · · · · · · ·	<del></del>	SECTION A		Well No.		
		CTION COMPANY	MUDGE PEDER		4		
Unit Letter D	Section 33	Township 27 NORTH	Range 11 WEST	County SAN JUA	N		
Actual Footage Lo	feet from the		and 1030	feet from the WES	T line		
Ground Level Elever 6218.7	r. Produci	ng Formation  DAKOTA	Pool	DAKOTA	Dedicated Acreage:		
who has the rig another. (65— 2. If the answer to wise? YES	Ref: GLO plat dated 19 July 1915  1. Is the Operator the only owner in the dedicated acreage outlined on the plat below? YES NO						
3. If the answer to	o question two	o is "no," list all the own	ers and their respective	interests below:	MAY16 to		
Owner			Land Desc	cription	367		
		SECTION B			CERTIFICATION		
	O - 7367 - O	33		in Splets beling the splets beling the splets below the s	Original signed by Carl W. Smith sition supt.  Appany otherst Production Co.  5/12/61		
				show plotte surve supe and and and Regi	reby certify that the well location we on the plat in SECTION B was ted from field notes of actual eys made by me or under my ervision, and that the same is true correct to the best of my knowledge belief.  Surveyed 12 May 1961 stered Professional Engineer or Land Surveyor  James P. Leese		
0 330 660 99	00 1320 165	0 1980 2310 2640 2	1500 1500 1000	300 0	ficate No. 1463 Juan Engineering Company		

## NSTRUCTIONS FOR COMPLETION OF FORM C-128

- 1. Operator s all furnish and certify to the information called for in Section A.
- 2. Operator s all outline the dedicated acreage for both oil and gas wells on the plat in Section B.
- 3. A register professional engineer or land surveyor registered in the State of New Mexico or approve by the Commission shall show on the plat the location of the well and certify this inform tion in the space provided.
- 4. All distan is shown on the plat must be from the outer boundaries of the Section.
- 5. If addition space is needed for listing owners and their respective interests as required in questio 3 of Section A, please use space below.