

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

SP-079113

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Atlantic Federal

9. WELL NO.

33-1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 33, T-27N, R-12W

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒

Wildcat

2. NAME OF OPERATOR

The Atlantic Refining Co.

3. ADDRESS OF OPERATOR

Box 2197, Farmington, N. M.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

NE NE (660' FNL & 560 FEL) Sec. 33

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 5822'

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following cement plugs were set on 12-20-63 through open ended drill pipe using measured displacement method.

From: 4925-4800' with 25 sacks class "C" cement plus 2% gel.

" 4050-3950' with 20 sacks class "C" cement plus 2% gel.

" 2150-2025' with 25 sacks class "C" cement plus 2% gel.

" 1300-1150' with 30 sacks class "C" cement plus 2% gel.

" 240- 150' with 30 sacks class "C" cement plus 2% gel.

(G.L.) 10' 30' with 10 sacks common cement

Intervals between cement plugs filled with drilling mud weighing 9.4#/gal. Put in dry hole marker.

Location was cleaned up on 2-10-64.

RECEIVED

FEB 20 1964

U. S. GEOLOGICAL SURVEY
FEB 20 1964

18. I hereby certify that the foregoing is true and correct

SIGNED

B. J. Sartain

TITLE Drilg. & Prod. Supv.

DATE 2-19-64

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

math of A

4582 10