



(SUBMIT IN TRIPLICATE)
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **060810**
Unit **Hamfano Unit**

SUNDRY NOTICES AND REPORTS ON WELLS

| | |
|--|--|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY |
| NOTICE OF INTENTION TO ABANDON WELL | |

RECEIVED
DEC 3 1958
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 1, 1958

Well No. **105** is located **800** ft. from **RR** line and **630** ft. from **E** line of sec. **22**

NE Sec. **29** (1/4 Sec. and Sec. No.)
27N (Twp.)
LOW (Range)
N.M.P.M. (Meridian)
Wildcat Dakota (Field)
San Juan (County or Subdivision)
New Mexico (State or Territory)

The elevation of the derrick floor above sea level is **6034** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

On 11-29-58. Total Depth 6543'.
Ran 19 joints 5 1/2", J-55, 17.0#, liner (804') set from 5736' to 6540' with 125 sacks regular cement, 125 sacks Pozmix, 1/4# Flocculo/sk, 6% Gel, followed with 5 sacks Mast cement.

Held 1000# for 30 minutes.

Top of cement by temperature survey at 5736'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997**
Farmington, New Mexico

By **Original Signed R. G. MILLER**

Title **Petroleum Engineer**

