

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P.O. Drawer 570, Farmington, NM 87499

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990' FSL & 990' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
NOV 15 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
U. S. GEOLOGICAL SURVEY

5. LEASE

NM -03465

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A.D. Hudson

9. WELL NO.

#3

10. FIELD OR WILDCAT NAME

Fulcher Kutz Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 29, T27N, R9W

12. COUNTY OR PARISH

13. STATE

San Juan

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

6385' DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-3-82 Rigged up and spotted 45 sacks cement plug from 2263' to 2000'.

11-4-82 Perf'd 5-1/2" casing at 1600' with four squeeze holes and squeeze with 50 sacks cement. Spot 11 sacks cement plug from 1600' to 1500'. Bradenhead squeezed with 50 sacks cement. Spot 10 sacks cement plug at surface.

11-5-82 Cut off casing 4' below surface and installed dry hole marker. Clean location.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engineer

DATE November 10, 1982

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

Instructions on Reverse Side

APPROVED
AS AMENDED

DEC 20 1984

M. MILLENBACH
AREA MANAGER