


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. SP-077951
Unit Jack Frost "C"



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF <u>4-1/2"</u>	<u>X</u>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Jack Frost "C"

Farmington, New Mexico January 24, 1963

Well No. 1 is located 1450 ft. from S line and 925 ft. from E line of sec. 26

NE/4 SE/4 Section 26
(1/4 Sec. and Sec. No.)

T-27N
(Twp.)

R-10W
(Range)

N.M.P.M.
(Meridian)

Basin Dakota
(Field)

San Juan
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6616 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

The above well was drilled to a total depth of 7023' and 4-1/2" casing was set at 7021' with 2 stage tool set at 2543'. First Stage was cemented with 250 sacks Quixtrench cement containing 4% gel and 1-1/2 pounds medium Tuf Plug per sack followed by 100 sacks neat cement. Second Stage was cemented with 600 sacks Quixtrench cement containing 4% gel. After waiting on cement, drilled out 2 stage tool and tested casing to 1000 pounds. Test ok.

Currently preparing to complete well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address P. O. Box 480

Farmington, New Mexico

Attn: L. O. Speer, Jr.

By

Title Petroleum Engineer