SF 077951 6. IF INDIAN, ALLOTTEE OR TRIBE NAME

5. FFASI

HIMITER CIATES

UNITED STATES				
DEPARTMENT	OF	THE	INTERIO	
GEOLOGICAL		SUR	VEY	

SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME		
(Do not use this form for proposals to drift on to deciped or plug back fit a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME		
1. oil gas well de well well well well well	Frost		
	9. WELL NO.		
2. NAME OF OPERATOR El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Fulcher Kutz Pictured Cliffs		
P. O. Box 990, Farmington, N. M. 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY, See space 17)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
below.) AT SURFACE: 1650'/S, 99'/E Sec. 26-27-10	Sec. 26, T27N, R10W 12. COUNTY OR PARISH 13. STATE San Juan New Mexico		
AT TOP PROD. INTERVAL:			
AT TOTAL DEPTH.	14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF.	6610' DF		
TEST WATER SHUT-OFF			
SHOOT OR ACIDIZE			
REPAIR WELL	(2011) Report results of multiple completion or zone		
PULL OR ALTER CASING LE MULTIPLE COMPLETE	ანგიცი ს ი Form 9 -ს30.)		
CHANGE ZONES () ABANDON*			
(other)			
17. DESCRIBE PROPOSED OR COMPLET D OFERATIONS (Clearly state including estimated date of starting any proposed work, if well is diameasured and true vertical depths for all markers and zones perticient.	and the second and the library of the second and th		
1. Pull 1" tubing and circulate well with 2" wo 2. Spot a 50 sk cement plug in the open hole se			
7" casing. (2292')			
3. Perforate 7" casing at 1700" with four shots cement plug at 1000 psi.	s and squeeze 84 sacks		
4. Shoot off 7" casing and recover 260' of 7" of	easing.		
5. Spot a 81 sack plug from 50' inside the cast			
the surface casing (83' to 310'). 6. Place a 10 sack surface plug and install a control of the surface casing (83' to 310').	dry halo marken		
7. Surface equipment will be removed and reseed	·		
year.	ed at the pest time of		
Subsurface Safety Valver Manur and Type	NOV 1 9: 1978 et 62		
18. Thereby certify that the foregoing is true and correct	MON 13 171		
SIGNED Was Ducken Total Engineer	DATE November 9, 1978		
This space for Foderal or State office			
APPROVED BY THE CONDITIONS OF APPROVAL, IF ANY	NOV 15 1913		
	/ NO. COL. 3		
*See histign floris on Reverse Sid	al all and		

NMOCC
*See Instructions on Reverse Side