



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 078092
Unit Cert. Localt 80

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Santa Fe</u> <u>11</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 2 is located 1350 ft. from N line and 790 ft. from W line of sec. 27
N 27 SEC. 27 27N 11W Range
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
West Lata Canyon San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6350 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Rigged up PGAC AND perforated 6497-6590 per 33 with 4 Atlas ball jets per foot. Rigged up Halliburton and sand fraced with 60,000# 20-40 in 60,300 gals. water with 1050 lb. MAC-6 and 6000 lb. Cal. Chloride. Broke down with 110 bbl. water at 12 BPM. Breakdown pressure 11901b. Sand started at 0.5 lb/gal. FYP 2900, dropped 35 rubber balls after inj. 30,000 lb., no appreciable press. increase. Dropped 15 more rubber balls after 35,500 lb. and 12 more after 36,000 lb. inj. Total pressure increase from 2225-2275. MFP 2900, AIN. TP 2100, ATP 2200, Avg. inj. rate 33.7 BPM. Flashed with 110 psi at 31 BPM. FYP 2725.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company The British-American Oil Prod. Co.

Address P.O. Drawer 330

Farmington, N.M.

By Mac A. Stone
Title Field Superintendent