

Reference Point - RDB El. 6110'

10'

Ground Level El. 6100'



495' of 9-5/8" 32.3# casing in
12-1/4" hole (cemented to surface)

Top of cement 1200'

2-stage cementing tool at 2061'

Top of cement 4010'

Gallup Perforations

(5438-5458 4 shots per foot)

(5538-5558 4 shots per foot)

(5613-5657 2 shots per foot)

(5704-5738 4 shots per foot)

5926' of 2-3/8" 4.7# tubing (with 2.910" O.D.
tapered couplings)

5890' of 3/4" sucker rods and pump

Baker Model "D" Retainer production packer
set at 6227'.

Dakota Perforations - 2 shots per foot

6362-6402 & 6419-6459

FBD - 6554'

FD - 6602' - 7" 23# & 20# casing in
8-3/4" hole

6357' of 2-3/8" 4.7# tub-
ing (with 2.910" O.D.
tapered couplings) with
Baker Model "E" Anchor
Tubing Seal Assembly

PAN AMERICAN PETROLEUM CORPORATION

C. A. McADAMS "B" NO. 1 - DIAGRAMATIC SKETCH OF DUAL COMPLETION EQUIP.

SCALE: None

RDB 5-20-59

DWG.
No.

— — — — —