



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. NM-03603-A
Unit Hammond

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 1, 1958

Hammond
Well No. 1 is located 1570 ft. from N line and 1140 ft. from E line of sec. 25
NE/4, Sec. 25 27N 8W N. M. P. M.
($\frac{1}{4}$ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco, Mesa Verde San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6003 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Mesa Verde gas well location - estimated T. D. 4650'
Equipment - 210' x 9 5/8" surface casing - 150 sacks cement
2400' x 7" intermediate casing - 150 sacks cement
2350' x 4 1/2" liner hung at 2350' - 150 sacks cement
Gamma Ray log to T. D. - perforate 100' of Point Lookout
Sand-water frac with 2000 barrels
4600' x 2" tubing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company R & G Drilling Company, Inc.

Address P. O. Box 1848

Farmington, New Mexico

By Maudine R. R. R.

Title Clerk