

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF-077973-C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Union Oil Company of California

3. ADDRESS OF OPERATOR

P. O. Box 2620 - Casper, Wyoming 82601

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1850' FNL & 1850' FWL (SE NW)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gov't Newman Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

San Juan Undesignated Field

11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA

Sec. 27, T. 27 N., R. 13 W.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6122' DF

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

☐
☐
☒
☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The subject well is no longer capable of production due to a casing leak between 3000' and 4000'. Cost of repairing the casing leak prohibits repairing this marginal well which prior to the leak was producing 8 BOPD on pump.

Proposed plugging procedure:

Cast iron BP at 5100' w/5 sxs. cmt. on top. (Unable to squeeze).

50 sx. plug across casing stub. 50' inside - 50' outside. Est. @ 3500'.

50 sx. plug across Picture Cliff from 1350-1450'.

50 sx. plug across base of Ojo Alamo from 690-790'.

35 sx. plug across base of surface pipe from 340-430'.

5 sx. plug at surface with marker.

Top of Point Lookout 3941'

Top of Picture Cliffs 1375'

Base of Ojo Alamo 759'

Casing Shoe 390'

Perforations: Gallup Sand - 5242-58' and 5262-66'.

18. I hereby certify that the foregoing is true and correct

SIGNED

T. N. Minette
T. N. Minette

TITLE

Drilling Engineer

DATE

1-28-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: