Form 9-331

Dec. 1973

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES

| OMILD SINILS | 5. LEASE |
|--|---|
| DEPARTMENT OF THE INTERIOR | SF 077951 A |
| GEOLOGICAL SURVEY | 6. IF INDIAN, ALLOTTEE OR TRIBE NAME |
| GLOCOGIONE CONVE | |
| CUMPRY NOTICES AND DEPORTS ON WELLS | 7. UNIT AGREEMENT NAME |
| SUNDRY NOTICES AND REPORTS ON WELLS | |
| (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) | 8. FARM OR LEASE NAME |
| | |
| 1. oil gas well other | Frost |
| MCR WCH CHICK | 9. WELL NO. |
| 2. NAME OF OPERATOR | #1 |
| El Paso Natural Gas Company | 10. FIELD OR WILDCAT NAME |
| 3. ADDRESS OF OPERATOR | Fulcher Kutz PC |
| P. O. Box 289, Farmington, New Mexico 87401 | 11. SEC., T., R., M., OR BLK. AND SURVEY OR |
| 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 | AREA |
| below.) | Section 26, T-27-N, R-10-W |
| AT SURFACE: 1750'N, 990'E | 12. COUNTY OR PARISH 13. STATE |
| AT TOP PROD. INTERVAL: AT TOTAL DEPTH: | San Juan New Mexico |
| | 14. API NO. |
| 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, | |
| REPORT, OR OTHER DATA | 15. ELEVATIONS (SHOW DF, KDB, AND WD) |
| | 6661 GL 3573 |
| REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: | |
| TEST WATER SHUT-OFF | |
| FRACTURE TREAT | 1 / |
| SHOOT OR ACIDIZE | Value 1 35 |
| REPAIR WELL PULL OR ALTER CASING | (NOTE: Report results of multiple completion or zone change on Form 9-330.) |
| MULTIPLE COMPLETE | |
| CHANGE ZONES | 는 사람들이 보고 <mark>무슨 기계를 하는 것이다. 그 사람들은 기계를 하는 것이다. 그 기계를 하는 것이다</mark> |
| ABANDON* XX DESERVE | CAL SURVEY : FRU TO GEORGE & TO |
| (other) FARMINGTO | NA, NA MA - 그 : 그랬다. 글 - 그는 연결했다 |
| And the state of t | |
| 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating and proposed work. If well is d | e all pertinent details, and give pertinent dates, |
| including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner | nt to this work.)* |
| 1) Circulate the well with mud. | |
| 2) Pull the 1" tubing and run a 2" work strip | nσ |
| 3) Spot a plug from T.D. (2558) to 2414'. | 78. 3 78.74 S 78.74 |
| 3) Spot a plug from 1.0. (2556) to 2414. | |
| 4) Spot a plug from 2110' to 2010' to cover the Fruitland. | |
| 5) Spot a plug from 1700' to 1600' to cover the Kirtland. | |
| 6) Perforate the 5 9/16" casing at 1525' and squeeze cement behind the casing | |
| to 1425'. Spot a plug from 1525' to 1425' to cover the Ojo Alamo. | |
| 7) Perforate the 5 9/16" casing at 170' and s | squeeze cement to the surface in |
| | a cement plug from 170' to |
| surface in the 5 9/16" casing. | |
| 8) Remove wellhead and install dry hole marks | er. jasiju gā izgaļ |
| 9) Remove surface equipment and restore surface | |
| , , , , , , , , , , , , , , , , , , , | 되왕하십다. 독립 연습교육 |
| Subsurface Safety Valve: Manu. and Type | |
| | 무리 그 그리고 얼마 되었다. |
| 18. I hereby certify that the foregoing is true and correct Production | |
| 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1 | DATE March 15, 1982 |
| SIGNED LITLE Engineer | DATE |
| pace for Federal or State off | fice use) 하늘목 관관 기술 기술 기술 기술 |
| | |
| CONDITIONS OF APPROVAL AND 3 1902. | DATE |
| | |

For JAMES F. SIMS DISTRICT ENGINEER

*See Instructions on Reverse Side