UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	Form Approved. Budget Bureau No. 42-R1424			
5.	LEASE			
	SF 077951A			
6.	IF INDIAN, ALLOTTEE OR TRIBE NAME			
	•			
7	UNIT AGREEMENT NAME			
8.	FARM OR LEASE NAME			
	Frost			
9.	WELL NO. #1			
10.	FIELD OR WILDCAT NAME			
	Fulcher Kutz PC			
11.	SEC., T., R., M., OR BLK. AND SURVEY OR AREA			
	Sec. 26, T-27-N, R-10-W			
12.	COUNTY OR PARISH 13. STATE			
	San Juan New Mexico			
14.	API NO.			
15.	ELEVATIONS (SHOW DF, KDB, AND WD)			
	6661' GL			
	OTE: Report results of multiple completion or zone change on Form 9–330.)			
103	2			

		-	LINIT ACDECTACATE	A A 4 =	
	IDRY NOTICES AND REPORTS ON WELLS		UNIT AGREEMENT N	AME	
(Do not use	e this form for proposals to drill or to differ or plug back to a different Jse Form 9–331–C for such proposals.)	1			
	AUG 01 1984	8.	FARM OR LEASE NAM	ИE	
1. oil	gas 🖂	<u>_</u>	Frost		
well	OII CON. LIV	9.	WELL NO.		
	E OF OPERATOR PICT 3		<u>#1</u>		
	1 430 Natural Gas Company	10. FIELD OR WILDCAT NAME			
	RESS OF OPERATOR	<u> </u>	Fulcher Kutz PC		
	. Box 289, Farmington, N.M. 87401	11.		BLK. AND SURVEY OR	
	ATION OF WELL (REPORT LOCATION CLEARLY. See space 17		AREA		
belov	•		Sec. 26, T-27-		
AT T	SURFACE: 1750'N, 990'E TOP PROD. INTERVAL:	12.	12. COUNTY OR PARISH 13. STATE		
	OTAL DEPTH:		San Juan	New Mexico	
16 0050	APPROPRIATE DOV. TO INDICATE MATURE OF MOTION	14.	API NO.		
	CK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, DRT, OR OTHER DATA				
KLFC	DRI, OR OTHER DATA	15.		DF, KDB, AND WD)	
REQUEST	FOR APPROVAL TO: SUBSEQUENT REPORT OF:		6661' GL		
-	TER SHUT-OFF				
	RE TREAT		· · · + 4		
	OR ACIDIZE	37	Parks.		
REPAIR \	WELL	(Ñ	OTE: Report results of m	ultiple completion or zone	
	R ALTER CASING []		change on Form 0	-330.)	
	E COMPLETE	15.3			
CHANGE ABANDOI					
(other)	N* L XI (c. d. sandanah				
(011101 <u>7</u>	2 1 1 1 1 1 1 1 1 1		en e	1	
17. DES	CRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stat	e all	pertinent details, and	give pertinent dates,	
inclu	iding estimated date of starting any proposed work. If well is d	irection	onally drilled, give sub	osurface locations and	
illea	sured and true vertical depths for all markers and zones pertiner	ιε το τ	nis work.)*		
1)	Circulate mud and spot a plug from TD to	o 24	14'.		
2)	Spot a plug from 2110' to 2010'.			7	
3)	Spot a plug from 1700' to 1600'.			:	
4)	Perforate the casing at 1525' and squee:	ze c	ement to 1425'	behind the	
	casing.		€ :		
5)	Spot a plug from 1525' to 1425' inside	the	casing.		
6)	Perforate the casing at 170' and squeeze			e inside the	
	8 5/8-5 9/16 annular space. Spot a plug				
	the 5 9/16" casing.				
7)	Remove wellhead and install a dry hole	mark	er.		
• •					
				\$	
				<u></u>	
Subsurfa	ice Safety Valve: Manu. and Type		Set	@ Ft.	
	, , , ,			<u> </u>	
18. I her	reby certify that the foregoing is true and correct Production				
SIGNED	William Willelmie Engineer		DATE June 8.	1082 1/IT	
SIGNED _	The Engineer		_ DATEJune 8.	DUVEL	
	(This space for Federal or State of	fice us) [] []	110	
				- 70. 4	

__ TITLE __

(SGD.) MAT MILLENBACH M. MILLENBAGER AREA MANAGER

NMOCC

*See Instructions on Reverse Side