Form	9-881	a
(Tab	1081	

 X	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

and Office	San	ta	Pe	
esse No.	MM	07	8478	_
Jnit				_

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DOUG	NECE; VE
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING 6 1958.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING DASING TO THE TITLE OF THE PORT OF ALTERING DASING TO THE TITLE OF THE PORT OF ALTERING DASING TO THE TITLE OF THE PORT OF ALTERING DASING TO THE TITLE OF THE PORT OF ALTERING DASING TO THE PORT OF THE POR
NOTICE OF INTENTION TO RE-DRILL OR REPAIR V	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT JFW ME
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY	CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	Ostober 2 19
Marron	
WIND A SIGN	ft. from $\left\{\begin{array}{c} N \\ S \end{array}\right\}$ line and $\frac{790}{100}$ ft. from $\left\{\begin{array}{c} E \\ W \end{array}\right\}$ line of sec. $\frac{27}{100}$
Well No. 4 is located 340	rt. from. (St) line and rt. from (W) line of sec
ww.h. 92 2	7-N 8-W KMPM
).) (Range) (Meridian)
So. Blanco Pictured Cliffs	San Juan New Mexico
(Field)	(County or Subdivision) (State or Territory)
Spudded well w/surface a pudd Set 36.25' of 8 5/8" 0.D. 25 Cemented pipe w/70 ax neat c	er on September 12, 1958. 65% Grade "B" Sals casing in 12 1/4" hole at 96° ement on September 18, 1958. 65% Grade "B" Sals casing in 12 1/4" hole at 96° ement on September 18, 1958. Gement circulated September 22, 1958 w/800% for 30 min. Held 0.K.
Spudded well w/surface a pudd Set 36.25' of 8 5/8" 0.D. 25 Cemented pipe w/70 ax neat c	er on September 12, 1958. .65# Grade "B" Smls casing in 12 1/4" hole at 96!
Spudded well w/surface a pudd Set 36.25' of 8 5/8* 0.D. 25 Cemented pipe w/70 sx neat c to surface. Tested pipe on	er on September 12, 1958. .65# Grade "B" Smls casing in 12 1/4" hole at 96!
Spudded well w/surface a pudd Set 36.25' of 8 5/8" 0.D. 25 Cemented pipe w/70 sx neat c to surface. Tested pipe on	er on September 12, 1958. .65# Grade "B" Smls casing in 12 1/4" hole at 96' ement on September 18, 1958. Gement circulated September 22, 1958 w/800# for 30 min. Held 0.K.
Spudded well w/surface a pudd Set 36.25' of 8 5/8" 0.D. 25 Cemented pipe w/70 sx neat c to surface. Tested pipe on lunderstand that this plan of work must receive Company WESTERN NATURAL	er on September 12, 1958. .65# Grade "B" Smls casing in 12 1/4" hole at 96' ement on September 18, 1958. Gement circulated September 22, 1958 w/800# for 30 min. Held 0.K.
Spudded well w/surface a pudd Set 36.25' of 8 5/8" O.D. 25 Cemented pipe w/70 sx neat c to surface. Tested pipe on I understand that this plan of work must receive Company WESTERN NATURAL	er on September 12, 1958. .65# Grade "B" Smls casing in 12 1/4" hole at 96' ement on September 18, 1958. Gement circulated September 22, 1958 w/800# for 30 min. Held 0.K. .approval in writing by the Geological Survey before operations may be commenced. GAS COMPANY