

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## LOCATE WELL CORRECTLY

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records. Original Signed R. G. MILLER  
Signed \_\_\_\_\_

The summary on this page is for the condition of the well at above date.

Commenced drilling 4-27-58, 1958 Finished drilling 5-8, 1958

No. 1, from 2091 to 2172 (G) No. 4, from 4363 to 4546 (G)  
No. 2, from 3702 to 3777 (G) No. 5, from to  
No. 3, from 3777 to 4363 (G) No. 6, from REF

No. 1, from \_\_\_\_\_ to \_\_\_\_\_ No. 3, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ No. 4, from \_\_\_\_\_ to \_\_\_\_\_

| Size casing | Weight per foot | Threads per inch | Make      | Amount | Kind of shoe | Cut and pulled from | Perforated |     | Purpose     |
|-------------|-----------------|------------------|-----------|--------|--------------|---------------------|------------|-----|-------------|
|             |                 |                  |           |        |              |                     | From—      | To— |             |
| 10 3/4      | 32.75           | P. E.            | S.W.      | 162    | Howco        |                     |            |     | Surface     |
| 7 5/8       | 26.4            | 8 Rd.            | J-55      | 2292   | Baker        |                     |            |     | Prod. Cng.  |
| 9 1/2       | 15.5            | 8 Rd.            | J-55      | 2349   | Baker        |                     |            |     | Prod. Liner |
| 2"          | 4.7             | 8 Rd.            | J-55      |        |              |                     |            |     | Prod. Tbg.  |
| 1 1/4"      | 2.4             | 8 Rd.            | Grade "A" |        |              |                     |            |     | Siphon      |

| Size casing | Where set | Number sacks of cement | Method used  | Mud gravity | Amount of mud used |
|-------------|-----------|------------------------|--------------|-------------|--------------------|
| 10 3/4      | 170       | 100                    | Circulated   |             |                    |
| 7 5/8       | 2264      | 200                    | Single Stage |             |                    |
| 5 1/2       | 2210-4559 | 300                    | Single Stage |             |                    |

Heaving plug—Material ..... Length ..... Depth set .....

Adapters—Material ..... Size **Guiberson "Shorty" Fkr. at 2326** .....

| <b>Size</b> | <b>Shell used</b> | <b>Explosive used</b>   | <b>Quantity</b> | <b>Date</b> | <b>Depth shot</b> | <b>Depth cleaned out</b> |
|-------------|-------------------|-------------------------|-----------------|-------------|-------------------|--------------------------|
|             |                   |                         |                 |             |                   |                          |
|             |                   | <b>See Well History</b> |                 |             |                   |                          |

Rotary tools were used from 175 feet to 2265 feet, and from 2265 feet to 4568 feet

Cable tools were used from 0 feet to 175 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

5-15, 19 58 Put to producing, 19

The production for the first 24 hours was ..... barrels of fluid of which .....% was oil; .....% emulsion; .....% water; and .....% sediment. Gravity, °Bé. ....

If gas well, cu. ft. per 24 hours FC 525,000  
MY 525,000 Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_

Rock pressure, lbs. per sq. in. **PC-7331-MV-1026** **A.C.F. = P.C. 527; M.V. 2610 MCF/D**

\_\_\_\_\_, Driller \_\_\_\_\_, Driller  
\_\_\_\_\_, Driller \_\_\_\_\_, Driller

| FROM— | TO—  | TOTAL FEET | FORMATION                                                                        |
|-------|------|------------|----------------------------------------------------------------------------------|
| 0     | 1197 | 1197       | Tan to gry cr-grn ss interbedded w/gry sh.                                       |
| 1197  | 1368 | 171        | Ojo Alamo ss. White cr-grn s.                                                    |
| 1368  | 1855 | 487        | Kirtland form. Gry sh interbedded w/tight gry fine-grn ss.                       |
| 1855  | 2091 | 236        | Fruitland form. Gry carb sh, scattered coals, coals and gry, tight, fine-grn ss. |
| 2091  | 2172 | 81         | Pictured Cliffs form. Gry, fine-grn, tight, varicolored soft ss.                 |
| 2172  | 3702 | 1530       | Lewis formation. Gry to white dense sh w/silty to shaly ss breaks.               |
| 3702  | 3777 | 75         | Cliff House ss. Gry, fine-grn dense sil ss.                                      |
| 3777  | 4363 | 586        | Manefee form. Gry, fine-grn s, carb sh & coal.                                   |
| 4363  | 4546 | 183        | Point Lookout form. Gry, very fine sil ss w/frequent sh breaks.                  |
| 4546  | 4568 | 22         | Mancos formation. Gry carban.                                                    |

